

GNU Libtool

For version 2.2.6, 1 August 2008

Gordon Matzigkeit
Alexandre Oliva
Thomas Tanner
Gary V. Vaughan

Copyright © 2008 Free Software Foundation, Inc.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or any later version published by the Free Software Foundation; with no Invariant Sections, with no Front-Cover Texts, and with no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

1 Introduction

In the past, if a source code package developer wanted to take advantage of the power of shared libraries, he needed to write custom support code for each platform on which his package ran. He also had to design a configuration interface so that the package installer could choose what sort of libraries were built.

GNU Libtool simplifies the developer's job by encapsulating both the platform-specific dependencies, and the user interface, in a single script. GNU Libtool is designed so that the complete functionality of each host type is available via a generic interface, but nasty quirks are hidden from the programmer.

GNU Libtool's consistent interface is reassuring... users don't need to read obscure documentation in order to have their favorite source package build shared libraries. They just run your package `configure` script (or equivalent), and libtool does all the dirty work.

There are several examples throughout this document. All assume the same environment: we want to build a library, `'libhello'`, in a generic way.

`'libhello'` could be a shared library, a static library, or both... whatever is available on the host system, as long as libtool has been ported to it.

This chapter explains the original design philosophy of libtool. Feel free to skip to the next chapter, unless you are interested in history, or want to write code to extend libtool in a consistent way.

1.1 Motivation for writing libtool

Since early 1995, several different GNU developers have recognized the importance of having shared library support for their packages. The primary motivation for such a change is to encourage modularity and reuse of code (both conceptually and physically) in GNU programs.

Such a demand means that the way libraries are built in GNU packages needs to be general, to allow for any library type the package installer might want. The problem is compounded by the absence of a standard procedure for creating shared libraries on different platforms.

The following sections outline the major issues facing shared library support in GNU, and how shared library support could be standardized with libtool.

The following specifications were used in developing and evaluating this system:

1. The system must be as elegant as possible.
2. The system must be fully integrated with the GNU Autoconf and Automake utilities, so that it will be easy for GNU maintainers to use. However, the system must not require these tools, so that it can be used by non-GNU packages.
3. Portability to other (non-GNU) architectures and tools is desirable.

1.2 Implementation issues

The following issues need to be addressed in any reusable shared library system, specifically libtool:

1. The package installer should be able to control what sort of libraries are built.

2. It can be tricky to run dynamically linked programs whose libraries have not yet been installed. `LD_LIBRARY_PATH` must be set properly (if it is supported), or programs fail to run.
3. The system must operate consistently even on hosts that don't support shared libraries.
4. The commands required to build shared libraries may differ wildly from host to host. These need to be determined at configure time in a consistent way.
5. It is not always obvious with what prefix or suffix a shared library should be installed. This makes it difficult for 'Makefile' rules, since they generally assume that file names are the same from host to host.
6. The system needs a simple library version number abstraction, so that shared libraries can be upgraded in place. The programmer should be informed how to design the interfaces to the library to maximize binary compatibility.
7. The install 'Makefile' target should warn the package installer to set the proper environment variables (`LD_LIBRARY_PATH` or equivalent), or run `ldconfig`.

1.3 Other implementations

Even before libtool was developed, many free software packages built and installed their own shared libraries. At first, these packages were examined to avoid reinventing existing features.

Now it is clear that none of these packages have documented the details of shared library systems that libtool requires. So, other packages have been more or less abandoned as influences.

1.4 A postmortem analysis of other implementations

In all fairness, each of the implementations that were examined do the job that they were intended to do, for a number of different host systems. However, none of these solutions seem to function well as a generalized, reusable component.

Most were too complex to use (much less modify) without understanding exactly what the implementation does, and they were generally not documented.

The main difficulty is that different vendors have different views of what libraries are, and none of the packages that were examined seemed to be confident enough to settle on a single paradigm that just *works*.

Ideally, libtool would be a standard that would be implemented as series of extensions and modifications to existing library systems to make them work consistently. However, it is not an easy task to convince operating system developers to mend their evil ways, and people want to build shared libraries right now, even on buggy, broken, confused operating systems.

For this reason, libtool was designed as an independent shell script. It isolates the problems and inconsistencies in library building that plague 'Makefile' writers by wrapping the compiler suite on different platforms with a consistent, powerful interface.

With luck, libtool will be useful to and used by the GNU community, and that the lessons that were learned in writing it will be taken up by designers of future library systems.

2 The libtool paradigm

At first, libtool was designed to support an arbitrary number of library object types. After libtool was ported to more platforms, a new paradigm gradually developed for describing the relationship between libraries and programs.

In summary, “libraries are programs with multiple entry points, and more formally defined interfaces.”

Version 0.7 of libtool was a complete redesign and rewrite of libtool to reflect this new paradigm. So far, it has proved to be successful: libtool is simpler and more useful than before.

The best way to introduce the libtool paradigm is to contrast it with the paradigm of existing library systems, with examples from each. It is a new way of thinking, so it may take a little time to absorb, but when you understand it, the world becomes simpler.

3 Using libtool

It makes little sense to talk about using libtool in your own packages until you have seen how it makes your life simpler. The examples in this chapter introduce the main features of libtool by comparing the standard library building procedure to libtool's operation on two different platforms:

'a23' An Ultrix 4.2 platform with only static libraries.

'burger' A NetBSD/i386 1.2 platform with shared libraries.

You can follow these examples on your own platform, using the preconfigured libtool script that was installed with libtool (see [Section 5.4 \[Configuring\]](#), page 24).

Source files for the following examples are taken from the 'demo' subdirectory of the libtool distribution. Assume that we are building a library, 'libhello', out of the files 'foo.c' and 'hello.c'.

Note that the 'foo.c' source file uses the `cos` math library function, which is usually found in the standalone math library, and not the C library (see [section "Trigonometric Functions" in *The GNU C Library Reference Manual*](#)). So, we need to add '-lm' to the end of the link line whenever we link 'foo.lo' into an executable or a library (see [Chapter 9 \[Inter-library dependencies\]](#), page 43).

The same rule applies whenever you use functions that don't appear in the standard C library. . . you need to add the appropriate '-lname' flag to the end of the link line when you link against those objects.

After we have built that library, we want to create a program by linking 'main.o' against 'libhello'.

3.1 Creating object files

To create an object file from a source file, the compiler is invoked with the '-c' flag (and any other desired flags):

```
burger$ gcc -g -O -c main.c
burger$
```

The above compiler command produces an object file, usually named 'main.o', from the source file 'main.c'.

For most library systems, creating object files that become part of a static library is as simple as creating object files that are linked to form an executable:

```
burger$ gcc -g -O -c foo.c
burger$ gcc -g -O -c hello.c
burger$
```

Shared libraries, however, may only be built from *position-independent code* (PIC). So, special flags must be passed to the compiler to tell it to generate PIC rather than the standard position-dependent code.

Since this is a library implementation detail, libtool hides the complexity of PIC compiler flags and uses separate library object files (the PIC one lives in the '.libs' subdirectory and the static one lives in the current directory). On systems without shared libraries, the

PIC library object files are not created, whereas on systems where all code is PIC, such as AIX, the static ones are not created.

To create library object files for `'foo.c'` and `'hello.c'`, simply invoke libtool with the standard compilation command as arguments (see [Section 4.1 \[Compile mode\]](#), page 15):

```
a23$ libtool --mode=compile gcc -g -O -c foo.c
gcc -g -O -c foo.c -o foo.o
a23$ libtool --mode=compile gcc -g -O -c hello.c
gcc -g -O -c hello.c -o hello.o
a23$
```

Note that libtool silently creates an additional control file on each `'compile'` invocation. The `'.lo'` file is the libtool object, which Libtool uses to determine what object file may be built into a shared library. On `'a23'`, only static libraries are supported so the library objects look like this:

```
# foo.lo - a libtool object file
# Generated by ltmain.sh (GNU libtool) 2.2.6
#
# Please DO NOT delete this file!
# It is necessary for linking the library.

# Name of the PIC object.
pic_object=none

# Name of the non-PIC object.
non_pic_object='foo.o'
```

On shared library systems, libtool automatically generates an additional PIC object by inserting the appropriate PIC generation flags into the compilation command:

```
burger$ libtool --mode=compile gcc -g -O -c foo.c
mkdir .libs
gcc -g -O -c foo.c -fPIC -DPIC -o .libs/foo.o
gcc -g -O -c foo.c -o foo.o >/dev/null 2>&1
burger$
```

Note that Libtool automatically created `'.libs'` directory upon its first execution, where PIC library object files will be stored.

Since `'burger'` supports shared libraries, and requires PIC objects to build them, Libtool has compiled a PIC object this time, and made a note of it in the libtool object:

```
# foo.lo - a libtool object file
# Generated by ltmain.sh (GNU libtool) 2.2.6
#
# Please DO NOT delete this file!
# It is necessary for linking the library.

# Name of the PIC object.
pic_object='.libs/foo.o'

# Name of the non-PIC object.
```

```
non_pic_object='foo.o'
```

Notice that the second run of GCC has its output discarded. This is done so that compiler warnings aren't annoyingly duplicated. If you need to see both sets of warnings (you might have conditional code inside `#ifdef PIC` for example), you can turn off suppression with the `'-no-suppress'` option to libtool's compile mode:

```
burger$ libtool --mode=compile gcc -no-suppress -g -O -c hello.c
gcc -g -O -c hello.c -fPIC -DPIC -o .libs/hello.o
gcc -g -O -c hello.c -o hello.o
burger$
```

3.2 Linking libraries

Without libtool, the programmer would invoke the `ar` command to create a static library:

```
burger$ ar cru libhello.a hello.o foo.o
burger$
```

But of course, that would be too simple, so many systems require that you run the `ranlib` command on the resulting library (to give it better karma, or something):

```
burger$ ranlib libhello.a
burger$
```

It seems more natural to use the C compiler for this task, given libtool's "libraries are programs" approach. So, on platforms without shared libraries, libtool simply acts as a wrapper for the system `ar` (and possibly `ranlib`) commands.

Again, the libtool control file name (`'lib.a'` suffix) differs from the standard library name (`'a'` suffix). The arguments to libtool are the same ones you would use to produce an executable named `'libhello.a'` with your compiler (see [Section 4.2 \[Link mode\]](#), page 16):

```
a23$ libtool --mode=link gcc -g -O -o libhello.a foo.o hello.o
*** Warning: Linking the shared library libhello.a against the non-libtool
*** objects foo.o hello.o is not portable!
ar cru .libs/libhello.a
ranlib .libs/libhello.a
creating libhello.a
(cd .libs && rm -f libhello.a && ln -s ../libhello.a libhello.a)
a23$
```

Aha! Libtool caught a common error... trying to build a library from standard objects instead of special `'lib.o'` object files. This doesn't matter so much for static libraries, but on shared library systems, it is of great importance. (Note that you may replace `'libhello.a'` with `'libhello.o'` in which case libtool won't issue the warning any more. But although this method works, this is not intended to be used because it makes you lose the benefits of using Libtool.)

So, let's try again, this time with the library object files. Remember also that we need to add `'-lm'` to the link command line because `'foo.c'` uses the `cos` math library function (see [Chapter 3 \[Using libtool\]](#), page 4).

Another complication in building shared libraries is that we need to specify the path to the directory in which they (eventually) will be installed (in this case, `‘/usr/local/lib’`)¹:

```
a23$ libtool --mode=link gcc -g -O -o libhello.la foo.lo hello.lo \
        -rpath /usr/local/lib -lm
ar cru .libs/libhello.a foo.o hello.o
ranlib .libs/libhello.a
creating libhello.la
(cd .libs && rm -f libhello.la && ln -s ../libhello.la libhello.la)
a23$
```

Now, let’s try the same trick on the shared library platform:

```
burger$ libtool --mode=link gcc -g -O -o libhello.la foo.lo hello.lo \
        -rpath /usr/local/lib -lm
rm -fr .libs/libhello.a .libs/libhello.la
ld -Bshareable -o .libs/libhello.so.0.0 .libs/foo.o .libs/hello.o -lm
ar cru .libs/libhello.a foo.o hello.o
ranlib .libs/libhello.a
creating libhello.la
(cd .libs && rm -f libhello.la && ln -s ../libhello.la libhello.la)
burger$
```

Now that’s significantly cooler... Libtool just ran an obscure `ld` command to create a shared library, as well as the static library.

Note how libtool creates extra files in the `‘.libs’` subdirectory, rather than the current directory. This feature is to make it easier to clean up the build directory, and to help ensure that other programs fail horribly if you accidentally forget to use libtool when you should.

Again, you may want to have a look at the `‘.la’` file in order to see what Libtool stores in it. In particular, you will see that Libtool uses this file to remember the destination directory for the library (the argument to `‘-rpath’`) as well as the dependency on the math library (`‘-lm’`).

3.3 Linking executables

If you choose at this point to *install* the library (put it in a permanent location) before linking executables against it, then you don’t need to use libtool to do the linking. Simply use the appropriate `‘-L’` and `‘-l’` flags to specify the library’s location.

Some system linkers insist on encoding the full directory name of each shared library in the resulting executable. Libtool has to work around this misfeature by special magic to ensure that only permanent directory names are put into installed executables.

The importance of this bug must not be overlooked: it won’t cause programs to crash in obvious ways. It creates a security hole, and possibly even worse, if you are modifying the library source code after you have installed the package, you will change the behaviour of the installed programs!

¹ If you don’t specify an `rpath`, then libtool builds a libtool convenience archive, not a shared library (see Section 3.7 [Static libraries], page 12).

So, if you want to link programs against the library before you install it, you must use libtool to do the linking.

Here's the old way of linking against an uninstalled library:

```
burger$ gcc -g -O -o hell.old main.o libhello.a -lm
burger$
```

Libtool's way is almost the same² (see Section 4.2 [Link mode], page 16):

```
a23$ libtool --mode=link gcc -g -O -o hell main.o libhello.la
gcc -g -O -o hell main.o ../libs/libhello.a -lm
a23$
```

That looks too simple to be true. All libtool did was transform 'libhello.la' to './libs/libhello.a', but remember that 'a23' has no shared libraries. Notice that Libtool also remembered that 'libhello.la' depends on '-lm', so even though we didn't specify '-lm' on the libtool command line³ Libtool has added it to the gcc link line for us.

On 'burger' Libtool links against the uninstalled shared library:

```
burger$ libtool --mode=link gcc -g -O -o hell main.o libhello.la
gcc -g -O -o .libs/hell main.o -L../libs -R/usr/local/lib -lhello -lm
creating hell
burger$
```

Now assume 'libhello.la' had already been installed, and you want to link a new program with it. You could figure out where it lives by yourself, then run:

```
burger$ gcc -g -O -o test test.o -L/usr/local/lib -lhello -lm
```

However, unless '/usr/local/lib' is in the standard library search path, you won't be able to run `test`. However, if you use libtool to link the already-installed libtool library, it will do The Right Thing (TM) for you:

```
burger$ libtool --mode=link gcc -g -O -o test test.o \
          /usr/local/lib/libhello.la
gcc -g -O -o .libs/test test.o -Wl,--rpath \
          -Wl,/usr/local/lib /usr/local/lib/libhello.a -lm
creating test
burger$
```

Note that libtool added the necessary run-time path flag, as well as '-lm', the library libhello.la depended upon. Nice, huh?

Notice that the executable, `hell`, was actually created in the '.libs' subdirectory. Then, a wrapper script was created in the current directory.

Since libtool created a wrapper script, you should use libtool to install it and debug it too. However, since the program does not depend on any uninstalled libtool library, it is probably usable even without the wrapper script.

On NetBSD 1.2, libtool encodes the installation directory of 'libhello', by using the '-R/usr/local/lib' compiler flag. Then, the wrapper script guarantees that the executable finds the correct shared library (the one in './libs') until it is properly installed.

² However, you should avoid using '-L' or '-l' flags to link against an uninstalled libtool library. Just specify the relative path to the '.la' file, such as './intl/libintl.la'. This is a design decision to eliminate any ambiguity when linking against uninstalled shared libraries.

³ And why should we? 'main.o' doesn't directly depend on '-lm' after all.

Let's compare the two different programs:

```
burger$ time ./hell.old
Welcome to GNU Hell!
** This is not GNU Hello.  There is no built-in mail reader. **
    0.21 real          0.02 user          0.08 sys
burger$ time ./hell
Welcome to GNU Hell!
** This is not GNU Hello.  There is no built-in mail reader. **
    0.63 real          0.09 user          0.59 sys
burger$
```

The wrapper script takes significantly longer to execute, but at least the results are correct, even though the shared library hasn't been installed yet.

So, what about all the space savings that shared libraries are supposed to yield?

```
burger$ ls -l hell.old libhello.a
-rwxr-xr-x  1 gord  gord  15481 Nov 14 12:11 hell.old
-rw-r--r--  1 gord  gord   4274 Nov 13 18:02 libhello.a
burger$ ls -l .libs/hell .libs/libhello.*
-rwxr-xr-x  1 gord  gord  11647 Nov 14 12:10 .libs/hell
-rw-r--r--  1 gord  gord   4274 Nov 13 18:44 .libs/libhello.a
-rwxr-xr-x  1 gord  gord  12205 Nov 13 18:44 .libs/libhello.so.0.0
burger$
```

Well, that sucks. Maybe I should just scrap this project and take up basket weaving.

Actually, it just proves an important point: shared libraries incur overhead because of their (relative) complexity. In this situation, the price of being dynamic is eight kilobytes, and the payoff is about four kilobytes. So, having a shared 'libhello' won't be an advantage until we link it against at least a few more programs.

3.4 Debugging executables

If 'hell' was a complicated program, you would certainly want to test and debug it before installing it on your system. In the above section, you saw how the libtool wrapper script makes it possible to run the program directly, but unfortunately, this mechanism interferes with the debugger:

```
burger$ gdb hell
GDB is free software and you are welcome to distribute copies of it
under certain conditions; type "show copying" to see the conditions.
There is no warranty for GDB; type "show warranty" for details.
GDB 4.16 (i386-unknown-netbsd), (C) 1996 Free Software Foundation, Inc.

"hell": not in executable format: File format not recognized

(gdb) quit
burger$
```

Sad. It doesn't work because GDB doesn't know where the executable lives. So, let's try again, by invoking GDB directly on the executable:

```

burger$ gdb .libs/hell
GNU gdb 5.3 (i386-unknown-netbsd)
Copyright 2002 Free Software Foundation, Inc.
GDB is free software, covered by the GNU General Public License,
and you are welcome to change it and/or distribute copies of it
under certain conditions. Type "show copying" to see the conditions.
There is no warranty for GDB. Type "show warranty" for details.
(gdb) break main
Breakpoint 1 at 0x8048547: file main.c, line 29.
(gdb) run
Starting program: /home/src/libtool/demo/.libs/hell
/home/src/libtool/demo/.libs/hell: can't load library 'libhello.so.0'

Program exited with code 020.
(gdb) quit
burger$

```

Argh. Now GDB complains because it cannot find the shared library that ‘hell’ is linked against. So, we must use libtool in order to properly set the library path and run the debugger. Fortunately, we can forget all about the ‘.libs’ directory, and just run it on the executable wrapper (see [Section 4.3 \[Execute mode\]](#), page 19):

```

burger$ libtool --mode=execute gdb hell
GNU gdb 5.3 (i386-unknown-netbsd)
Copyright 2002 Free Software Foundation, Inc.
GDB is free software, covered by the GNU General Public License,
and you are welcome to change it and/or distribute copies of it
under certain conditions. Type "show copying" to see the conditions.
There is no warranty for GDB. Type "show warranty" for details.
(gdb) break main
Breakpoint 1 at 0x8048547: file main.c, line 29.
(gdb) run
Starting program: /home/src/libtool/demo/.libs/hell

Breakpoint 1, main (argc=1, argv=0xbffffc40) at main.c:29
29      printf ("Welcome to GNU Hell!\n");
(gdb) quit
The program is running. Quit anyway (and kill it)? (y or n) y
burger$

```

3.5 Installing libraries

Installing libraries on a non-libtool system is quite straightforward... just copy them into place:⁴

```

burger$ su
Password: *****
burger# cp libhello.a /usr/local/lib/libhello.a

```

⁴ Don't strip static libraries though, or they will be unusable.

```
burger#
```

Oops, don't forget the `ranlib` command:

```
burger# ranlib /usr/local/lib/libhello.a
burger#
```

Libtool installation is quite simple, as well. Just use the `install` or `cp` command that you normally would (see [Section 4.4 \[Install mode\]](#), page 19):

```
a23# libtool --mode=install cp libhello.la /usr/local/lib/libhello.la
cp libhello.la /usr/local/lib/libhello.la
cp .libs/libhello.a /usr/local/lib/libhello.a
ranlib /usr/local/lib/libhello.a
a23#
```

Note that the libtool library 'libhello.la' is also installed, to help libtool with uninstillation (see [Section 4.6 \[Uninstall mode\]](#), page 20) and linking (see [Section 3.3 \[Linking executables\]](#), page 7) and to help programs with dlopening (see [Chapter 10 \[Dlopened modules\]](#), page 44).

Here is the shared library example:

```
burger# libtool --mode=install install -c libhello.la \
        /usr/local/lib/libhello.la
install -c .libs/libhello.so.0.0 /usr/local/lib/libhello.so.0.0
install -c libhello.la /usr/local/lib/libhello.la
install -c .libs/libhello.a /usr/local/lib/libhello.a
ranlib /usr/local/lib/libhello.a
burger#
```

It is safe to specify the `-s` (strip symbols) flag if you use a BSD-compatible install program when installing libraries. Libtool will either ignore the `-s` flag, or will run a program that will strip only debugging and compiler symbols from the library.

Once the libraries have been put in place, there may be some additional configuration that you need to do before using them. First, you must make sure that where the library is installed actually agrees with the `-rpath` flag you used to build it.

Then, running `'libtool -n finish libdir'` can give you further hints on what to do (see [Section 4.5 \[Finish mode\]](#), page 20):

```
burger# libtool -n finish /usr/local/lib
PATH="$PATH:/sbin" ldconfig -m /usr/local/lib
```

```
-----
Libraries have been installed in:
  /usr/local/lib
```

To link against installed libraries in a given directory, `LIBDIR`, you must use the `-LLIBDIR` flag during linking.

You will also need to do one of the following:

- add `LIBDIR` to the `'LD_LIBRARY_PATH'` environment variable during execution
- add `LIBDIR` to the `'LD_RUN_PATH'` environment variable

```

    during linking
    - use the '-RLIBDIR' linker flag

```

See any operating system documentation about shared libraries for more information, such as the `ld` and `ld.so` manual pages.

```
-----
burger#
```

After you have completed these steps, you can go on to begin using the installed libraries. You may also install any executables that depend on libraries you created.

3.6 Installing executables

If you used `libtool` to link any executables against uninstalled `libtool` libraries (see [Section 3.3 \[Linking executables\]](#), page 7), you need to use `libtool` to install the executables after the libraries have been installed (see [Section 3.5 \[Installing libraries\]](#), page 10).

So, for our Ultrix example, we would run:

```

a23# libtool --mode=install -c hell /usr/local/bin/hell
install -c hell /usr/local/bin/hell
a23#

```

On shared library systems that require wrapper scripts, `libtool` just ignores the wrapper script and installs the correct binary:

```

burger# libtool --mode=install -c hell /usr/local/bin/hell
install -c .libs/hell /usr/local/bin/hell
burger#

```

3.7 Linking static libraries

Why return to `ar` and `ranlib` silliness when you've had a taste of `libtool`? Well, sometimes it is desirable to create a static archive that can never be shared. The most frequent case is when you have a set of object files that you use to build several different libraries. You can create a “convenience library” out of those objects, and link against that with the other libraries, instead of listing all the object files every time.

If you just want to link this convenience library into programs, then you could just ignore `libtool` entirely, and use the old `ar` and `ranlib` commands (or the corresponding GNU Automake `'_LIBRARIES'` rules). You can even install a convenience library using GNU Libtool, though you probably don't want to and hence GNU Automake doesn't allow you to do so.

```

burger$ libtool --mode=install ./install-sh -c libhello.a \
      /local/lib/libhello.a
./install-sh -c libhello.a /local/lib/libhello.a
ranlib /local/lib/libhello.a
burger$

```

Using `libtool` for static library installation protects your library from being accidentally stripped (if the installer used the `'-s'` flag), as well as automatically running the correct `ranlib` command.

But libtool libraries are more than just collections of object files: they can also carry library dependency information, which old archives do not. If you want to create a libtool static convenience library, you can omit the `-rpath` flag and use `-static` to indicate that you're only interested in a static library. When you link a program with such a library, libtool will actually link all object files and dependency libraries into the program.

If you omit both `-rpath` and `-static`, libtool will create a convenience library that can be used to create other libtool libraries, even shared ones. Just like in the static case, the library behaves as an alias to a set of object files and dependency libraries, but in this case the object files are suitable for inclusion in shared libraries. But be careful not to link a single convenience library, directly or indirectly, into a single program or library, otherwise you may get errors about symbol redefinitions.

The key is remembering that a convenience library contains PIC objects, and can be linked where a list of PIC objects makes sense; i.e. into a shared library. A static convenience library contains non-PIC objects, so can be linked into an old static library, or a program.

When GNU Automake is used, you should use `noinst_LTLIBRARIES` instead of `lib_LTLIBRARIES` for convenience libraries, so that the `-rpath` option is not passed when they are linked.

As a rule of thumb, link a libtool convenience library into at most one libtool library, and never into a program, and link libtool static convenience libraries only into programs, and only if you need to carry library dependency information to the user of the static convenience library.

Another common situation where static linking is desirable is in creating a standalone binary. Use libtool to do the linking and add the `-all-static` flag.

4 Invoking libtool

The libtool program has the following synopsis:

```
libtool [option]... [mode-arg]...
```

and accepts the following options:

- '--config'
Display libtool configuration variables and exit.
- '--debug' Dump a trace of shell script execution to standard output. This produces a lot of output, so you may wish to pipe it to `less` (or `more`) or redirect to a file.
- '-n'
- '--dry-run'
Don't create, modify, or delete any files, just show what commands would be executed by libtool.
- '--features'
Display basic configuration options. This provides a way for packages to determine whether shared or static libraries will be built.
- '--finish'
Same as '--mode=finish'.
- '--help' Display a help message and exit. If '--mode=mode' is specified, then detailed help for *mode* is displayed.
- '--mode=mode'
Use *mode* as the operation mode. When using libtool from the command line, you can give just *mode* (or a unique abbreviation of it) as the first argument as a shorthand for the full '--mode=mode'.
mode must be set to one of the following:
 - 'compile' Compile a source file into a libtool object.
 - 'execute' Automatically set the library path so that another program can use uninstalled libtool-generated programs or libraries.
 - 'finish' Complete the installation of libtool libraries on the system.
 - 'install' Install libraries or executables.
 - 'link' Create a library or an executable.
 - 'uninstall'
Delete installed libraries or executables.
 - 'clean' Delete uninstalled libraries or executables.
- '--tag=tag'
Use configuration variables from tag *tag* (see [Section 6.2 \[Tags\]](#), page 35).
- '--preserve-dup-deps'
Do not remove duplicate dependencies in libraries. When building packages with static libraries, the libraries may depend circularly on each other (shared

libs can too, but for those it doesn't matter), so there are situations, where `-la` `-lb` `-la` is required, and the second `-la` may not be stripped or the link will fail. In cases where these duplications are required, this option will preserve them, only stripping the libraries that libtool knows it can safely.

`--quiet`
`--silent`

Do not print out any progress or informational messages.

`-v`
`--verbose`

Print out progress and informational messages (enabled by default).

`--version`

Print libtool version information and exit.

The *mode-args* are a variable number of arguments, depending on the selected operation mode. In general, each *mode-arg* is interpreted by programs libtool invokes, rather than libtool itself.

4.1 Compile mode

For *compile* mode, *mode-args* is a compiler command to be used in creating a “standard” object file. These arguments should begin with the name of the C compiler, and contain the `-c` compiler flag so that only an object file is created.

Libtool determines the name of the output file by removing the directory component from the source file name, then substituting the source code suffix (e.g. `.c` for C source code) with the library object suffix, `.lo`.

If shared libraries are being built, any necessary PIC generation flags are substituted into the compilation command.

The following components of *mode-args* are treated specially:

`-o` Note that the `-o` option is now fully supported. It is emulated on the platforms that don't support it (by locking and moving the objects), so it is really easy to use libtool, just with minor modifications to your Makefiles. Typing for example

```
libtool --mode=compile gcc -c foo/x.c -o foo/x.lo
```

will do what you expect.

Note, however, that, if the compiler does not support `-c` and `-o`, it is impossible to compile `foo/x.c` without overwriting an existing `./x.o`. Therefore, if you do have a source file `./x.c`, make sure you introduce dependencies in your `Makefile` to make sure `./x.o` (or `./x.lo`) is re-created after any sub-directory's `x.lo`:

```
x.o x.lo: foo/x.lo bar/x.lo
```

This will also ensure that make won't try to use a temporarily corrupted `x.o` to create a program or library. It may cause needless recompilation on platforms that support `-c` and `-o` together, but it's the only way to make it safe for those that don't.

- ‘`-no-suppress`’
If both PIC and non-PIC objects are being built, libtool will normally suppress the compiler output for the PIC object compilation to save showing very similar, if not identical duplicate output for each object. If the ‘`-no-suppress`’ option is given in compile mode, libtool will show the compiler output for both objects.
- ‘`-prefer-pic`’
Libtool will try to build only PIC objects.
- ‘`-prefer-non-pic`’
Libtool will try to build only non-PIC objects.
- ‘`-shared`’
Even if Libtool was configured with ‘`--enable-static`’, the object file Libtool builds will not be suitable for static linking. Libtool will signal an error if it was configured with ‘`--disable-shared`’, or if the host does not support shared libraries.
- ‘`-static`’
Even if libtool was configured with ‘`--disable-static`’, the object file Libtool builds **will** be suitable for static linking.
- ‘`-Wc, flag`’
‘`-Xcompiler flag`’
Pass a linker specific flag directly to the compiler.
- ‘`-Wl, flag`’
‘`-Xlinker flag`’
Pass a linker specific flag directly to the linker.
- ‘`-XCCLinker flag`’
Pass a link specific flag to the compiler driver (*CC*) during linking.

4.2 Link mode

Link mode links together object files (including library objects) to form another library or to create an executable program.

mode-args consist of a command using the C compiler to create an output file (with the ‘`-o`’ flag) from several object files.

The following components of *mode-args* are treated specially:

- ‘`-all-static`’
If *output-file* is a program, then do not link it against any shared libraries at all. If *output-file* is a library, then only create a static library. In general, this flag cannot be used together with ‘`disable-static`’ (see [Section 5.4.1 \[LT_INIT\]](#), [page 25](#)).
- ‘`-avoid-version`’
Tries to avoid versioning (see [Chapter 7 \[Versioning\]](#), [page 37](#)) for libraries and modules, i.e. no version information is stored and no symbolic links are created. If the platform requires versioning, this option has no effect.
- ‘`-dlopen file`’
Same as ‘`-dlpreopen file`’, if native dlopening is not supported on the host platform (see [Chapter 10 \[Dlopened modules\]](#), [page 44](#)) or if the program is

linked with `‘-static’`, `‘-static-libtool-libs’`, or `‘-all-static’`. Otherwise, no effect. If *file* is `self` Libtool will make sure that the program can `dlopen` itself, either by enabling `‘-export-dynamic’` or by falling back to `‘-dlpreopen self’`.

`‘-dlpreopen file’`

Link *file* into the output program, and add its symbols to the list of preloaded symbols (see [Section 10.2 \[Dlpreopening\]](#), page 44). If *file* is `self`, the symbols of the program itself will be added to preloaded symbol lists. If *file* is `force` Libtool will make sure that a preloaded symbol list is always *defined*, regardless of whether it’s empty or not.

`‘-export-dynamic’`

Allow symbols from *output-file* to be resolved with `dlsym` (see [Chapter 10 \[Dlopened modules\]](#), page 44).

`‘-export-symbols symfile’`

Tells the linker to export only the symbols listed in *symfile*. The symbol file should end in `‘.sym’` and must contain the name of one symbol per line. This option has no effect on some platforms. By default all symbols are exported.

`‘-export-symbols-regex regex’`

Same as `‘-export-symbols’`, except that only symbols matching the regular expression *regex* are exported. By default all symbols are exported.

`‘-Llibdir’`

Search *libdir* for required libraries that have already been installed.

`‘-lname’` *output-file* requires the installed library `‘libname’`. This option is required even when *output-file* is not an executable.

`‘-module’` Creates a library that can be `dlopened` (see [Chapter 10 \[Dlopened modules\]](#), page 44). This option doesn’t work for programs. Module names don’t need to be prefixed with `‘lib’`. In order to prevent name clashes, however, `‘libname’` and `‘name’` must not be used at the same time in your package.

`‘-no-fast-install’`

Disable fast-install mode for the executable *output-file*. Useful if the program won’t be necessarily installed.

`‘-no-install’`

Link an executable *output-file* that can’t be installed and therefore doesn’t need a wrapper script on systems that allow hardcoding of library paths. Useful if the program is only used in the build tree, e.g., for testing or generating other files.

`‘-no-undefined’`

Declare that *output-file* does not depend on any other libraries. Some platforms cannot create shared libraries that depend on other libraries (see [Chapter 9 \[Inter-library dependencies\]](#), page 43).

`‘-o output-file’`

Create *output-file* from the specified objects and libraries.

- ‘-objectlist *file*’
Use a list of object files found in *file* to specify objects.
- ‘-precious-files-regex *regex*’
Prevents removal of files from the temporary output directory whose names match this regular expression. You might specify ‘\.**bbg**?\$’ to keep those files created with `gcc -ftest-coverage` for example.
- ‘-release *release*’
Specify that the library was generated by release *release* of your package, so that users can easily tell which versions are newer than others. Be warned that no two releases of your package will be binary compatible if you use this flag. If you want binary compatibility, use the ‘-version-info’ flag instead (see [Chapter 7 \[Versioning\]](#), page 37).
- ‘-rpath *libdir*’
If *output-file* is a library, it will eventually be installed in *libdir*. If *output-file* is a program, add *libdir* to the run-time path of the program.
- ‘-R *libdir*’
If *output-file* is a program, add *libdir* to its run-time path. If *output-file* is a library, add ‘-R*libdir*’ to its *dependency_libs*, so that, whenever the library is linked into a program, *libdir* will be added to its run-time path.
- ‘-shared’
If *output-file* is a program, then link it against any uninstalled shared libtool libraries (this is the default behavior). If *output-file* is a library, then only create a shared library. In the later case, libtool will signal an error if it was configured with ‘--disable-shared’, or if the host does not support shared libraries.
- ‘-shrext *suffix*’
If *output-file* is a libtool library, replace the system’s standard file name extension for shared libraries with *suffix* (most systems use ‘.so’ here). This option is helpful in certain cases where an application requires that shared libraries (typically modules) have an extension other than the default one. Please note you must supply the full file name extension including any leading dot.
- ‘-static’
If *output-file* is a program, then do not link it against any uninstalled shared libtool libraries. If *output-file* is a library, then only create a static library.
- ‘-static-libtool-libs’
If *output-file* is a program, then do not link it against any shared libtool libraries. If *output-file* is a library, then only create a static library.
- ‘-version-info *current*[:*revision*][:*age*]]’
If *output-file* is a libtool library, use interface version information *current*, *revision*, and *age* to build it (see [Chapter 7 \[Versioning\]](#), page 37). Do **not** use this flag to specify package release information, rather see the ‘-release’ flag.
- ‘-version-number *major*[:*minor*][:*revision*]]’
If *output-file* is a libtool library, compute interface version information so that the resulting library uses the specified major, minor and revision numbers. This

is designed to permit libtool to be used with existing projects where identical version numbers are already used across operating systems. New projects should use the ‘`-version-info`’ flag instead.

‘`-weak libname`’

if *output-file* is a libtool library, declare that it provides a weak *libname* interface. This is a hint to libtool that there is no need to append *libname* to the list of dependency libraries of *output-file*, because linking against *output-file* already supplies the same interface (see [Section 10.3 \[Linking with dlopened modules\]](#), page 47).

‘`-Wl, flag`’

‘`-Xlinker flag`’

Pass a linker specific flag directly to the linker.

‘`-XCCLinker flag`’

Pass a link specific flag to the compiler driver (*CC*) during linking.

If the *output-file* ends in ‘`.la`’, then a libtool library is created, which must be built only from library objects (‘`.lo`’ files). The ‘`-rpath`’ option is required. In the current implementation, libtool libraries may not depend on other uninstalled libtool libraries (see [Chapter 9 \[Inter-library dependencies\]](#), page 43).

If the *output-file* ends in ‘`.a`’, then a standard library is created using `ar` and possibly `ranlib`.

If *output-file* ends in ‘`.o`’ or ‘`.lo`’, then a reloadable object file is created from the input files (generally using ‘`ld -r`’). This method is often called *partial linking*.

Otherwise, an executable program is created.

4.3 Execute mode

For *execute* mode, the library path is automatically set, then a program is executed.

The first of the *mode-args* is treated as a program name, with the rest as arguments to that program.

The following components of *mode-args* are treated specially:

‘`-dlopen file`’

Add the directory containing *file* to the library path.

This mode sets the library path environment variable according to any ‘`-dlopen`’ flags.

If any of the *args* are libtool executable wrappers, then they are translated into the name of their corresponding uninstalled binary, and any of their required library directories are added to the library path.

4.4 Install mode

In *install* mode, libtool interprets most of the elements of *mode-args* as an installation command beginning with `cp`, or a BSD-compatible `install` program.

The following components of *mode-args* are treated specially:

`'-inst-prefix inst-prefix-dir'`

When installing into a temporary staging area, rather than the final *prefix*, this argument is used to reflect the temporary path, in much the same way *automake* uses *DESTDIR*. For instance, if *prefix* is `'/usr/local'`, but *inst-prefix-dir* is `'/tmp'`, then the object will be installed under `'/tmp/usr/local/'`. If the installed object is a libtool library, then the internal fields of that library will reflect only *prefix*, not *inst-prefix-dir*:

```
# Directory that this library needs to be installed in:
libdir='/usr/local/lib'
```

not

```
# Directory that this library needs to be installed in:
libdir='/tmp/usr/local/lib'
```

inst-prefix is also used to insure that if the installed object must be re-linked upon installation, that it is re-linked against the libraries in *inst-prefix-dir/prefix*, not *prefix*.

In truth, this option is not really intended for use when calling libtool directly; it is automatically used when `libtool --mode=install` calls `libtool --mode=relink`. Libtool does this by analyzing the destination path given in the original `libtool --mode=install` command and comparing it to the expected installation path established during `libtool --mode=link`.

Thus, end-users need change nothing, and *automake*-style `make install DESTDIR=/tmp` will Just Work(tm) most of the time. For systems where fast installation can not be turned on, relinking may be needed. In this case, a `'DESTDIR'` install will fail.

Currently it is not generally possible to install into a temporary staging area that contains needed third-party libraries which are not yet visible at their final location.

The rest of the *mode-args* are interpreted as arguments to the `cp` or `install` command.

The command is run, and any necessary unprivileged post-installation commands are also completed.

4.5 Finish mode

Finish mode helps system administrators install libtool libraries so that they can be located and linked into user programs.

Each *mode-arg* is interpreted as the name of a library directory. Running this command may require superuser privileges, so the `'--dry-run'` option may be useful.

4.6 Uninstall mode

Uninstall mode deletes installed libraries, executables and objects.

The first *mode-arg* is the name of the program to use to delete files (typically `/bin/rm`).

The remaining *mode-args* are either flags for the deletion program (beginning with a `'-'`), or the names of files to delete.

4.7 Clean mode

Clean mode deletes uninstalled libraries, executables, objects and `libtool`'s temporary files associated with them.

The first *mode-arg* is the name of the program to use to delete files (typically `/bin/rm`).

The remaining *mode-args* are either flags for the deletion program (beginning with a '-'), or the names of files to delete.

5 Integrating libtool with your package

This chapter describes how to integrate libtool with your packages so that your users can install hassle-free shared libraries.

5.1 Autoconf macros exported by libtool

Libtool uses a number of macros to interrogate the host system when it is being built, and you can use some of them yourself too. Although there are a great many other macros in the libtool installed m4 files, these do not form part of the published interface, and are subject to change between releases.

Macros in the ‘LT_CMD_’ namespace check for various shell commands:

LT_CMD_MAX_LEN [Macro]
 Finds the longest command line that can be safely passed to ‘\$SHELL’ without being truncated, and store in the shell variable ‘\$max_cmd_len’. It is only an approximate value, but command lines of this length or shorter are guaranteed not to be truncated.

Macros in the ‘LT_FUNC_’ namespace check characteristics of library functions:

LT_FUNC_DLSYM_USCORE [Macro]
 ‘AC_DEFINE’ the preprocessor symbol ‘DLSYM_USCORE’ if we have to add an underscore to symbol-names passed in to ‘dlsym’.

Macros in the ‘LT_LIB_’ namespace check characteristics of system libraries:

LT_LIB_M [Macro]
 Set ‘LIBM’ to the math library or libraries required on this machine, if any.

LT_LIB_DLOAD [Macro]
 This is the macro used by ‘libltdl’ to determine which dloaders to use on this machine, if any. Several shell variables are set (and ‘AC_SUBST’ed) depending on the dload interfaces are available on this machine. ‘LT_DLLOADERS’ contains a list of libtool libraries that can be used, and if necessary also sets ‘LIBADD_DLOPEN’ if additional system libraries are required by the ‘dlopen’ loader, and ‘LIBADD_SHL_LOAD’ if additional system libraries are required by the ‘shl_load’ loader, respectively. Finally some symbols are set in ‘config.h’ depending on the loaders that are found to work: ‘HAVE_LIBDL’, ‘HAVE_SHL_LOAD’, ‘HAVE_DYLD’, ‘HAVE_DLD’.

Macros in the ‘LT_PATH_’ namespace search the system for the full path to particular system commands:

LT_PATH_LD [Macro]
 Add a ‘--with-gnu-ld’ option to ‘configure’. Try to find the path to the linker used by ‘\$CC’, and whether it is the GNU linker. The result is stored in the shell variable ‘\$LD’, which is AC_SUBSTed.

LT_PATH_NM [Macro]
 Try to find a BSD compatible `nm` or a MS compatible `dumpbin` command on this machine. The result is stored in the shell variable ‘\$NM’, which is AC_SUBSTed.

Macros in the ‘LT_SYS_’ namespace probe for system characteristics:

- LT_SYS_DLOPEN_SELF** [Macro]
 Tests whether a program can dlopen itself, and then also whether the same program can still dlopen itself when statically linked. Results are stored in the shell variables ‘\$enable_dlopen_self’ and ‘enable_dlopen_self_static’ respectively.
- LT_SYS_DLOPEN_DEPLIBS** [Macro]
 Define the preprocessor symbol ‘LTDL_DLOPEN_DEPLIBS’ if the OS needs help to load dependent libraries for ‘dlopen’ (or equivalent).
- LT_SYS_DLSEARCH_PATH** [Macro]
 Define the preprocessor symbol ‘LT_DLSEARCH_PATH’ to the system default library search path.
- LT_SYS_MODULE_EXT** [Macro]
 Define the preprocessor symbol ‘LT_MODULE_EXT’ to the extension used for runtime loadable modules. If you use libltdl to open modules, then you can simply use the libtool library extension, ‘.la’.
- LT_SYS_MODULE_PATH** [Macro]
 Define the preprocessor symbol ‘LT_MODULE_PATH_VAR’ to the name of the shell environment variable that determines the run-time module search path.
- LT_SYS_SYMBOL_USCORE** [Macro]
 Set the shell variable ‘sys_symbol_underscore’ to ‘no’ unless the compiler prefixes global symbols with an underscore.

5.2 Writing ‘Makefile’ rules for libtool

Libtool is fully integrated with Automake (see [section “Introduction” in *The Automake Manual*](#)), starting with Automake version 1.2.

If you want to use libtool in a regular ‘Makefile’ (or ‘Makefile.in’), you are on your own. If you’re not using Automake, and you don’t know how to incorporate libtool into your package you need to do one of the following:

1. Download the latest Automake distribution from your nearest GNU mirror, install it, and start using it.
2. Learn how to write ‘Makefile’ rules by hand. They’re sometimes complex, but if you’re clever enough to write rules for compiling your old libraries, then you should be able to figure out new rules for libtool libraries (hint: examine the ‘Makefile.in’ in the ‘tests/demo’ subdirectory of the libtool distribution. . . note especially that it was automatically generated from the ‘Makefile.am’ by Automake).

5.3 Using Automake with libtool

Libtool library support is implemented under the ‘LTLIBRARIES’ primary.

Here are some samples from the Automake ‘Makefile.am’ in the libtool distribution’s ‘demo’ subdirectory.

First, to link a program against a libtool library, just use the ‘`program_LDADD`’¹ variable:

```
bin_PROGRAMS = hell hell_static

# Build hell from main.c and libhello.la
hell_SOURCES = main.c
hell_LDADD = libhello.la

# Create a statically linked version of hell.
hell_static_SOURCES = main.c
hell_static_LDADD = libhello.la
hell_static_LDFLAGS = -static
```

You may use the ‘`program_LDFLAGS`’ variable to stuff in any flags you want to pass to libtool while linking ‘`program`’ (such as ‘`-static`’ to avoid linking uninstalled shared libtool libraries).

Building a libtool library is almost as trivial. . . note the use of ‘`libhello_la_LDFLAGS`’ to pass the ‘`-version-info`’ (see [Chapter 7 \[Versioning\]](#), page 37) option to libtool:

```
# Build a libtool library, libhello.la for installation in libdir.
lib_LTLIBRARIES = libhello.la
libhello_la_SOURCES = hello.c foo.c
libhello_la_LDFLAGS = -version-info 3:12:1
```

The ‘`-rpath`’ option is passed automatically by Automake (except for libraries listed as `noinst_LTLIBRARIES`), so you should not specify it.

See section “The Automake Manual” in *The Automake Manual*, for more information.

5.4 Configuring libtool

Libtool requires intimate knowledge of your compiler suite and operating system in order to be able to create shared libraries and link against them properly. When you install the libtool distribution, a system-specific libtool script is installed into your binary directory.

However, when you distribute libtool with your own packages (see [Section 5.5 \[Distributing\]](#), page 31), you do not always know the compiler suite and operating system that are used to compile your package.

For this reason, libtool must be *configured* before it can be used. This idea should be familiar to anybody who has used a GNU `configure` script. `configure` runs a number of tests for system features, then generates the ‘`Makefile`’s (and possibly a ‘`config.h`’ header file), after which you can run `make` and build the package.

Libtool adds its own tests to your `configure` script in order to generate a libtool script for the installer’s host machine.

¹ Since GNU Automake 1.5, the flags ‘`-dlopen`’ or ‘`-dlpreopen`’ (see [Section 4.2 \[Link mode\]](#), page 16) can be employed with the `program_LDADD` variable. Unfortunately, older releases didn’t accept these flags, so if you are stuck with an ancient Automake, we recommend quoting the flag itself, and setting `program_DEPENDENCIES` too:

```
program_LDADD = "-dlopen" libfoo.la
program_DEPENDENCIES = libfoo.la
```

5.4.1 The LT_INIT macro

If you are using GNU Autoconf (or Automake), you should add a call to `LT_INIT` to your ‘`configure.ac`’ file. This macro adds many new tests to the `configure` script so that the generated libtool script will understand the characteristics of the host. It’s the most important of a number of macros defined by Libtool:

`LT_PREREQ` (*VERSION*) [Macro]

Ensure that a recent enough version of Libtool is being used. If the version of Libtool used for `LT_INIT` is earlier than *version*, print an error message to the standard error output and exit with failure (exit status is 63). For example:

```
LT_PREREQ([2.2.6])
```

`LT_INIT` (*OPTIONS*) [Macro]

`AC_PROG_LIBTOOL` [Macro]

`AM_PROG_LIBTOOL` [Macro]

Add support for the ‘`--enable-shared`’ and ‘`--disable-shared`’ `configure` flags.² `AC_PROG_LIBTOOL` and `AM_PROG_LIBTOOL` are deprecated names for older versions of this macro; `autoupdate` will upgrade your ‘`configure.ac`’ files.

By default, this macro turns on shared libraries if they are available, and also enables static libraries if they don’t conflict with the shared libraries. You can modify these defaults by passing either `disable-shared` or `disable-static` in the option list to `LT_INIT`, or using `AC_DISABLE_SHARED` or `AC_DISABLE_STATIC`.

```
# Turn off shared libraries during beta-testing, since they
# make the build process take too long.
LT_INIT([disable-shared])
```

The user may specify modified forms of the `configure` flags ‘`--enable-shared`’ and ‘`--enable-static`’ to choose whether shared or static libraries are built based on the name of the package. For example, to have shared ‘`bfd`’ and ‘`gdb`’ libraries built, but not shared ‘`libg++`’, you can run all three `configure` scripts as follows:

```
trick$ ./configure --enable-shared=bfd,gdb
```

In general, specifying ‘`--enable-shared=pkgs`’ is the same as configuring with ‘`--enable-shared`’ every package named in the comma-separated *pkgs* list, and every other package with ‘`--disable-shared`’. The ‘`--enable-static=pkgs`’ flag behaves similarly, but it uses ‘`--enable-static`’ and ‘`--disable-static`’. The same applies to the ‘`--enable-fast-install=pkgs`’ flag, which uses ‘`--enable-fast-install`’ and ‘`--disable-fast-install`’.

The package name ‘`default`’ matches any packages that have not set their name in the `PACKAGE` environment variable.

This macro also sets the shell variable `LIBTOOL_DEPS`, that you can use to automatically update the libtool script if it becomes out-of-date. In order to do that, add to your ‘`configure.ac`’:

² `LT_INIT` requires that you define the ‘`Makefile`’ variable `top_builddir` in your ‘`Makefile.in`’. Automake does this automatically, but Autoconf users should set it to the relative path to the top of your build directory (‘`../..`’, for example).

```
LT_INIT
AC_SUBST([LIBTOOL_DEPS])
```

and, to `Makefile.in` or `Makefile.am`:

```
LIBTOOL_DEPS = @LIBTOOL_DEPS@
libtool: $(LIBTOOL_DEPS)
    $(SHELL) ./config.status --recheck
```

If you are using GNU Automake, you can omit the assignment, as Automake will take care of it. You'll obviously have to create some dependency on `libtool`.

Aside from `disable-static` and `disable-shared`, there are other options that you can pass to `LT_INIT` to modify its behaviour. Here is a full list:

`'dlopen'` Enable checking for `dlopen` support. This option should be used if the package makes use of the `'-dlopen'` and `'-dlpreopen'` libtool flags, otherwise libtool will assume that the system does not support `dlopen`.

`'win32-dll'`

This option should be used if the package has been ported to build clean dlls on win32 platforms. Usually this means that any library data items are exported with `__declspec(dllexport)` and imported with `__declspec(dllimport)`. If this macro is not used, libtool will assume that the package libraries are not dll clean and will build only static libraries on win32 hosts.

Provision must be made to pass `'-no-undefined'` to `libtool` in link mode from the package `Makefile`. Naturally, if you pass `'-no-undefined'`, you must ensure that all the library symbols **really are** defined at link time!

`'disable-fast-install'`

Change the default behaviour for `LT_INIT` to disable optimization for fast installation. The user may still override this default, depending on platform support, by specifying `'--enable-fast-install'` to `configure`.

`'shared'`

Change the default behaviour for `LT_INIT` to enable shared libraries. This is the default on all systems where Libtool knows how to create shared libraries. The user may still override this default by specifying `'--disable-shared'` to `configure`.

`'disable-shared'`

Change the default behaviour for `LT_INIT` to disable shared libraries. The user may still override this default by specifying `'--enable-shared'` to `configure`.

`'static'`

Change the default behaviour for `LT_INIT` to enable static libraries. This is the default on all systems where shared libraries have been disabled for some reason, and on most systems where shared libraries have been enabled. If shared libraries are enabled, the user may still override this default by specifying `'--disable-static'` to `configure`.

`'disable-static'`

Change the default behaviour for `LT_INIT` to disable static libraries. The user may still override this default by specifying `'--enable-static'` to `configure`.

- `'pic-only'` Change the default behaviour for `libtool` to try to use only PIC objects. The user may still override this default by specifying `'--without-pic'` to `configure`.
- `'no-pic'` Change the default behaviour of `libtool` to try to use only non-PIC objects. The user may still override this default by specifying `'--with-pic'` to `configure`.

`LT_LANG (LANGUAGE)` [Macro]

Enable `libtool` support for the language given if it has not yet already been enabled. Languages accepted are “C++”, “Fortran 77”, “Java” and “Windows Resource”.

If Autoconf language support macros such as `AC_PROG_CXX` are used in your `'configure.ac'`, Libtool language support will automatically be enabled.

Conversely using `LT_LANG` to enable language support for Libtool will automatically enable Autoconf language support as well.

Both of the following examples are therefore valid ways of adding C++ language support to Libtool.

```
LT_INIT
LT_LANG([C++])

LT_INIT
AC_PROG_CXX
```

`AC_LIBTOOL_DLOPEN` [Macro]

This macro is deprecated, the `'dlopen'` option to `LT_INIT` should be used instead.

`AC_LIBTOOL_WIN32_DLL` [Macro]

This macro is deprecated, the `'win32-dll'` option to `LT_INIT` should be used instead.

`AC_DISABLE_FAST_INSTALL` [Macro]

This macro is deprecated, the `'disable-fast-install'` option to `LT_INIT` should be used instead.

`AC_DISABLE_SHARED` [Macro]

`AM_DISABLE_SHARED` [Macro]

Change the default behaviour for `LT_INIT` to disable shared libraries. The user may still override this default by specifying `'--enable-shared'`. The option `'disable-shared'` to `LT_INIT` is a shorthand for this. `AM_DISABLE_SHARED` is a deprecated alias for `AC_DISABLE_SHARED`.

`AC_ENABLE_SHARED` [Macro]

`AM_ENABLE_SHARED` [Macro]

Change the default behaviour for `LT_INIT` to enable shared libraries. This is the default on all systems where Libtool knows how to create shared libraries. The user may still override this default by specifying `'--disable-shared'`. The option `'shared'` to `LT_INIT` is a shorthand for this. `AM_ENABLE_SHARED` is a deprecated alias for `AC_ENABLE_SHARED`.

AC_DISABLE_STATIC [Macro]

AM_DISABLE_STATIC [Macro]

Change the default behaviour for `LT_INIT` to disable static libraries. The user may still override this default by specifying `--enable-static`. The option `'disable-static'` to `LT_INIT` is a shorthand for this. `AM_DISABLE_STATIC` is a deprecated alias for `AC_DISABLE_STATIC`.

AC_ENABLE_STATIC [Macro]

AM_ENABLE_STATIC [Macro]

Change the default behaviour for `LT_INIT` to enable static libraries. This is the default on all systems where shared libraries have been disabled for some reason, and on most systems where shared libraries have been enabled. If shared libraries are enabled, the user may still override this default by specifying `--disable-static`. The option `'static'` to `LT_INIT` is a shorthand for this. `AM_ENABLE_STATIC` is a deprecated alias for `AC_ENABLE_STATIC`.

The tests in `LT_INIT` also recognize the following environment variables:

CC [Variable]

The C compiler that will be used by the generated `libtool`. If this is not set, `LT_INIT` will look for `gcc` or `cc`.

CFLAGS [Variable]

Compiler flags used to generate standard object files. If this is not set, `LT_INIT` will not use any such flags. It affects only the way `LT_INIT` runs tests, not the produced `libtool`.

CPPFLAGS [Variable]

C preprocessor flags. If this is not set, `LT_INIT` will not use any such flags. It affects only the way `LT_INIT` runs tests, not the produced `libtool`.

LD [Variable]

The system linker to use (if the generated `libtool` requires one). If this is not set, `LT_INIT` will try to find out what is the linker used by `CC`.

LDFLAGS [Variable]

The flags to be used by `libtool` when it links a program. If this is not set, `LT_INIT` will not use any such flags. It affects only the way `LT_INIT` runs tests, not the produced `libtool`.

LIBS [Variable]

The libraries to be used by `LT_INIT` when it links a program. If this is not set, `LT_INIT` will not use any such flags. It affects only the way `LT_INIT` runs tests, not the produced `libtool`.

NM [Variable]

Program to use rather than checking for `nm`.

RANLIB [Variable]

Program to use rather than checking for `ranlib`.

- LN_S** [Variable]
 A command that creates a link of a program, a soft-link if possible, a hard-link otherwise. `LT_INIT` will check for a suitable program if this variable is not set.
- DLLTOOL** [Variable]
 Program to use rather than checking for `dlltool`. Only meaningful for Cygwin/MS-Windows.
- OBJDUMP** [Variable]
 Program to use rather than checking for `objdump`. Only meaningful for Cygwin/MS-Windows.
- AS** [Variable]
 Program to use rather than checking for `as`. Only used on Cygwin/MS-Windows at the moment.

With 1.3 era libtool, if you wanted to know any details of what libtool had discovered about your architecture and environment, you had to run the script with `--config` and grep through the results. This idiom was supported up to and including 1.5.x era libtool, where it was possible to call the generated libtool script from `configure.ac` as soon as `LT_INIT` had completed. However, one of the features of libtool 1.4 was that the libtool configuration was migrated out of a separate `ltconfig` file, and added to the `LT_INIT` macro (nee `AC_PROG_LIBTOOL`), so the results of the configuration tests were available directly to code in `configure.ac`, rendering the call out to the generated libtool script obsolete.

Starting with libtool 2.0, the multipass generation of the libtool script has been consolidated into a single `config.status` pass, which happens after all the code in `configure.ac` has completed. The implication of this is that the libtool script does not exist during execution of code from `configure.ac`, and so obviously it cannot be called for `--config` details anymore. If you are upgrading projects that used this idiom to libtool 2.0 or newer, you should replace those calls with direct references to the equivalent Autoconf shell variables that are set by the configure time tests before being passed to `config.status` for inclusion in the generated libtool script.

LT_OUTPUT [Macro]
 By default, the configured `libtool` script is generated by the call to `AC_OUTPUT` command, and there is rarely any need to use `libtool` from `configure`. However, sometimes it is necessary to run configure time compile and link tests using `libtool`. You can add `LT_OUTPUT` to your `configure.ac` any time after `LT_INIT` and any `LT_LANG` calls; that done, `libtool` will be created by a specially generated `config.lt` file, and available for use in later tests.

Also, when `LT_OUTPUT` is used, for backwards compatibility with Automake regeneration rules, `config.status` will call `config.lt` to regenerate `libtool`, rather than generating the file itself.

When you invoke the `libtoolize` program (see [Section 5.5.1 \[Invoking libtoolize\]](#), [page 31](#)), it will tell you where to find a definition of `LT_INIT`. If you use Automake, the `aclocal` program will automatically add `LT_INIT` support to your `configure` script when it sees the invocation of `LT_INIT` in `configure.ac`.

Because of these changes, and the runtime version compatibility checks Libtool now executes, we now advise **against** including a copy of ‘libtool.m4’ (and brethren) in ‘acinclude.m4’. Instead, you should set your project macro directory with `AC_CONFIG_MACRO_DIR`. When you `libtoolize` your project, a copy of the relevant macro definitions will be placed in your `AC_CONFIG_MACRO_DIR`, where `aclocal` can reference them directly from ‘aclocal.m4’.

5.4.2 Platform-specific configuration notes

While Libtool tries to hide as many platform-specific features as possible, some have to be taken into account when configuring either the Libtool package or a libtoolized package.

- You currently need GNU make to build the Libtool package itself.
- On AIX there are two different styles of shared linking, one in which symbols are bound at link-time and one in which symbols are bound at runtime only, similar to ELF. In case of doubt use `LDFLAGS=-Wl,-brtl` for the latter style.
- On AIX, native tools are to be preferred over binutils; especially for C++ code, if using the AIX Toolbox GCC 4.0 and binutils, configure with `AR=/usr/bin/ar LD=/usr/bin/ld NM='/usr/bin/nm -B'`.
- On AIX, the `/bin/sh` is very slow due to its inefficient handling of here-documents. A modern shell is preferable:

```
CONFIG_SHELL=/bin/bash; export $CONFIG_SHELL
$CONFIG_SHELL ./configure [...]
```

- For C++ code with templates, it may be necessary to specify the way the compiler will generate the instantiations. For Portland pgCC version5, use `CXX='pgCC --one_instantiation_per_object'` and avoid parallel `make`.
- On Darwin, for C++ code with templates you need two level shared libraries. Libtool builds these by default if `MACOSX_DEPLOYMENT_TARGET` is set to 10.3 or later at `configure` time. See rdar://problem/4135857 for more information on this issue.
- The default shell on UNICOS 9, a ksh 88e variant, is too buggy to correctly execute the libtool script. Users are advised to install a modern shell such as GNU bash.
- Some HP-UX `sed` programs are horribly broken, and cannot handle libtool’s requirements, so users may report unusual problems. There is no workaround except to install a working `sed` (such as GNU `sed`) on these systems.
- The vendor-distributed NCR MP-RAS `cc` programs emits copyright on standard error that confuse tests on size of ‘`conftest.err`’. The workaround is to specify `CC` when run `configure` with `CC='cc -Hnocopyr'`.
- Any earlier DG/UX system with ELF executables, such as R3.10 or R4.10, is also likely to work, but hasn’t been explicitly tested.
- On Reliant Unix libtool has only been tested with the Siemens C-compiler and an old version of `gcc` provided by Marco Walther.
- ‘libtool.m4’, ‘ltdl.m4’ and the ‘`configure.ac`’ files are marked to use `autoconf`-mode, which is distributed with GNU Emacs 21, Autoconf itself, and all recent releases of XEmacs.
- When building on some linux systems for multilib targets `libtool` sometimes guesses the wrong paths that the linker and dynamic linker search by default. If this occurs, you

may override libtool's guesses at `configure` time by setting the `autoconf` cache variables `lt_cv_sys_lib_search_path_spec` and `lt_cv_sys_lib_dlsearch_path_spec` respectively to the correct search paths.

5.5 Including libtool in your package

In order to use libtool, you need to include the following files with your package:

- '`config.guess`'
Attempt to guess a canonical system name.
- '`config.sub`'
Canonical system name validation subroutine script.
- '`install-sh`'
BSD-compatible `install` replacement script.
- '`ltmain.sh`'
A generic script implementing basic libtool functionality.

Note that the libtool script itself should *not* be included with your package. See [Section 5.4 \[Configuring\], page 24](#).

You should use the `libtoolize` program, rather than manually copying these files into your package.

5.5.1 Invoking libtoolize

The `libtoolize` program provides a standard way to add libtool support to your package. In the future, it may implement better usage checking, or other features to make libtool even easier to use.

The `libtoolize` program has the following synopsis:

```
libtoolize [option]...
```

and accepts the following options:

- '`--copy`'
- '`-c`' Copy files from the libtool data directory rather than creating symlinks.
- '`--debug`' Dump a trace of shell script execution to standard output. This produces a lot of output, so you may wish to pipe it to `less` (or `more`) or redirect to a file.
- '`--dry-run`'
- '`-n`' Don't run any commands that modify the file system, just print them out.
- '`--force`'
- '`-f`' Replace existing libtool files. By default, `libtoolize` won't overwrite existing files.
- '`--help`' Display a help message and exit.
- '`--ltdl [TARGET-DIRECTORY-NAME]`'
Install `libltdl` in the `TARGET-DIRECTORY-NAME` subdirectory of your package. Normally, the directory is extracted from the argument to `LT_CONFIG_LTDL_DIR` in '`configure.ac`', though you can also specify a subdirectory name here if you are not using Autoconf for example. If `libtoolize` can't determine the target directory, '`libltdl`' is used as the default.

`--no-warn`

Normally, Libtoolize tries to diagnose use of deprecated libtool macros and other stylistic issues. If you are deliberately using outdated calling conventions, this option prevents Libtoolize from explaining how to update your project's Libtool conventions.

`--nonrecursive`

If passed in conjunction with `--ltdl`, this option will cause the `libltdl` installed by `libtoolize` to be set up for use with a non-recursive `automake` build. To make use of it, you will need to add the following to the `Makefile.am` of the parent project:

```
## libltdl/Makefile.inc appends to the following variables
## so we set them here before including it:
BUILT_SOURCES    =

AM_CPPFLAGS      =
AM_LDFLAGS       =

include_HEADERS  =
noinst_LTLIBRARIES =
lib_LTLIBRARIES  =
EXTRA_LTLIBRARIES =

EXTRA_DIST      =

CLEANFILES      =
MOSTLYCLEANFILES =

include libltdl/Makefile.inc
```

`--quiet`

`-q`

Work silently. `libtoolize --quiet` is used by GNU Automake to add libtool files to your package if necessary.

`--recursive`

If passed in conjunction with `--ltdl`, this option will cause the `libtoolize` installed `libltdl` to be set up for use with a recursive `automake` build. To make use of it, you will need to adjust the parent project's `configure.ac`:

```
AC_CONFIG_FILES([libltdl/Makefile])
```

and `Makefile.am`:

```
SUBDIRS += libltdl
```

`--subproject`

If passed in conjunction with `--ltdl`, this option will cause the `libtoolize` installed `libltdl` to be set up for independent configuration and compilation as a self-contained subproject. To make use of it, you should arrange for your build to call `libltdl/configure`, and then run `make` in the `libltdl` directory (or the subdirectory you put `libltdl` into). If your project uses Autoconf, you

can use the supplied ‘`LT_WITH_LTDL`’ macro, or else call ‘`AC_CONFIG_SUBDIRS`’ directly.

Previous releases of ‘`libltdl`’ built exclusively in this mode, but now it is the default mode both for backwards compatibility and because, for example, it is suitable for use in projects that wish to use ‘`libltdl`’, but not use the Autotools for their own build process.

‘`--verbose`’

‘`-v`’ Work noisily! Give a blow by blow account of what `libtoolize` is doing.

‘`--version`’

Print `libtoolize` version information and exit.

Sometimes it can be useful to pass options to `libtoolize` even though it is called by another program, such as `autoreconf`. A limited number of options are parsed from the environment variable `LIBTOOLIZE_OPTIONS`: currently ‘`--debug`’, ‘`--no-warn`’, ‘`--quiet`’ and ‘`--verbose`’. Multiple options passed in `LIBTOOLIZE_OPTIONS` must be separated with a space, comma or a colon.

By default, a warning is issued for unknown options found in `LIBTOOLIZE_OPTIONS` unless the first such option is ‘`--no-warn`’. Where `libtoolize` has always quit on receipt of an unknown option at the command line, this and all previous releases of `libtoolize` will continue unabated whatever the content of `LIBTOOLIZE_OPTIONS` (modulo some possible warning messages).

```
trick$ LIBTOOLIZE_OPTIONS=--no-warn,--quiet autoreconf --install
```

If `libtoolize` detects an explicit call to `AC_CONFIG_MACRO_DIR` (see [section “The Autoconf Manual”](#) in *The Autoconf Manual*) in your ‘`configure.ac`’, it will put the Libtool macros in the specified directory.

In the future other Autotools will automatically check the contents of `AC_CONFIG_MACRO_DIR`, but at the moment it is more portable to add the macro directory to `ACLOCAL_AMFLAGS` in ‘`Makefile.am`’, which is where the tools currently look. If `libtoolize` doesn’t see `AC_CONFIG_MACRO_DIR`, it too will honour the first ‘`-I`’ argument in `ACLOCAL_AMFLAGS` when choosing a directory to store libtool configuration macros in. It is perfectly sensible to use both `AC_CONFIG_MACRO_DIR` and `ACLOCAL_AMFLAGS`, as long as they are kept in synchronisation.

```
ACLOCAL_AMFLAGS = -I m4
```

When you bootstrap your project with `aclocal`, then you will need to explicitly pass the same macro directory with `aclocal`’s ‘`-I`’ flag:

```
trick$ aclocal -I m4
```

If `libtoolize` detects an explicit call to `AC_CONFIG_AUX_DIR` (see [section “The Autoconf Manual”](#) in *The Autoconf Manual*) in your ‘`configure.ac`’, it will put the other support files in the specified directory. Otherwise they too end up in the project root directory.

Unless ‘`--no-warn`’ is passed, `libtoolize` displays hints for adding libtool support to your package, as well.

5.5.2 Autoconf and LTLIBOBJ

People used to add code like the following to their ‘`configure.ac`’:

```
LTLIBOBJS='echo "$LIBOBJS" | sed 's/\.[^.]* /\.lo /g;s/\.[^.]*$/\.lo/'
AC_SUBST([LTLIBOBJS])
```

This is no longer required (since Autoconf 2.54), and doesn't take Automake's deansification support into account either, so doesn't work correctly even with ancient Autoconfs!

Provided you are using a recent (2.54 or better) incarnation of Autoconf, the call to `AC_OUTPUT` takes care of setting `LTLIBOBJS` up correctly, so you can simply delete such snippets from your `configure.ac` if you had them.

5.6 Static-only libraries

When you are developing a package, it is often worthwhile to configure your package with the `--disable-shared` flag, or to override the defaults for `LT_INIT` by using the `disable-shared` option (see [Section 5.4.1 \[The `LT_INIT` macro\], page 25](#)). This prevents libtool from building shared libraries, which has several advantages:

- compilation is twice as fast, which can speed up your development cycle,
- debugging is easier because you don't need to deal with any complexities added by shared libraries, and
- you can see how libtool behaves on static-only platforms.

You may want to put a small note in your package `README` to let other developers know that `--disable-shared` can save them time. The following example note is taken from the GIMP³ distribution `README`:

```
The GIMP uses GNU Libtool in order to build shared libraries on a
variety of systems. While this is very nice for making usable
binaries, it can be a pain when trying to debug a program. For that
reason, compilation of shared libraries can be turned off by
specifying the '--disable-shared' option to 'configure'.
```

³ GNU Image Manipulation Program, for those who haven't taken the plunge. See <http://www.gimp.org/>.

6 Using libtool with other languages

Libtool was first implemented in order to add support for writing shared libraries in the C language. However, over time, libtool is being integrated with other languages, so that programmers are free to reap the benefits of shared libraries in their favorite programming language.

This chapter describes how libtool interacts with other languages, and what special considerations you need to make if you do not use C.

6.1 Writing libraries for C++

Creating libraries of C++ code should be a fairly straightforward process, because its object files differ from C ones in only three ways:

1. Because of name mangling, C++ libraries are only usable by the C++ compiler that created them. This decision was made by the designers of C++ in order to protect users from conflicting implementations of features such as constructors, exception handling, and RTTI.
2. On some systems, the C++ compiler must take special actions for the dynamic linker to run dynamic (i.e., run-time) initializers. This means that we should not call `ld` directly to link such libraries, and we should use the C++ compiler instead.
3. C++ compilers will link some Standard C++ library in by default, but libtool does not know which are these libraries, so it cannot even run the inter-library dependence analyzer to check how to link it in. Therefore, running `ld` to link a C++ program or library is deemed to fail.

Because of these three issues, Libtool has been designed to always use the C++ compiler to compile and link C++ programs and libraries. In some instances the `main()` function of a program must also be compiled with the C++ compiler for static C++ objects to be properly initialized.

6.2 Tags

Libtool supports multiple languages through the use of tags. Technically a tag corresponds to a set of configuration variables associated with a language. These variables tell libtool how it should create objects and libraries for each language.

Tags are defined at `configure`-time for each language activated in the package (see `LT_LANG` in Section 5.4.1 [LT_INIT], page 25). Here is the correspondence between language names and tags names.

| Language name | Tag name |
|------------------|----------|
| C | CC |
| C++ | CXX |
| Java | G CJ |
| Fortran 77 | F77 |
| Fortran | FC |
| Windows Resource | RC |

libtool tries to automatically infer which tag to use from the compiler command being used to compile or link. If it can't infer a tag, then it defaults to the configuration for the C language.

The tag can also be specified using `libtool`'s `'--tag=tag'` option (see [Chapter 4 \[Invoking libtool\]](#), page 14). It is a good idea to do so in `'Makefile'` rules, because that will allow users to substitute the compiler without relying on `libtool` inference heuristics. When no tag is specified, `libtool` will default to `CC`; this tag always exists.

Finally, the set of tags available in a particular project can be retrieved by tracing for the `LT_SUPPORTED_TAG` macro (see [Chapter 12 \[Trace interface\]](#), page 70).

7 Library interface versions

The most difficult issue introduced by shared libraries is that of creating and resolving runtime dependencies. Dependencies on programs and libraries are often described in terms of a single name, such as `sed`. So, one may say “libtool depends on `sed`,” and that is good enough for most purposes.

However, when an interface changes regularly, we need to be more specific: “Gnus 5.1 requires Emacs 19.28 or above.” Here, the description of an interface consists of a name, and a “version number.”

Even that sort of description is not accurate enough for some purposes. What if Emacs 20 changes enough to break Gnus 5.1?

The same problem exists in shared libraries: we require a formal version system to describe the sorts of dependencies that programs have on shared libraries, so that the dynamic linker can guarantee that programs are linked only against libraries that provide the interface they require.

7.1 What are library interfaces?

Interfaces for libraries may be any of the following (and more):

- global variables: both names and types
- global functions: argument types and number, return types, and function names
- standard input, standard output, standard error, and file formats
- sockets, pipes, and other inter-process communication protocol formats

Note that static functions do not count as interfaces, because they are not directly available to the user of the library.

7.2 Libtool’s versioning system

Libtool has its own formal versioning system. It is not as flexible as some, but it is definitely the simplest of the more powerful versioning systems.

Think of a library as exporting several sets of interfaces, arbitrarily represented by integers. When a program is linked against a library, it may use any subset of those interfaces.

Libtool’s description of the interfaces that a program uses is simple: it encodes the least and the greatest interface numbers in the resulting binary (*first-interface*, *last-interface*).

The dynamic linker is guaranteed that if a library supports *every* interface number between *first-interface* and *last-interface*, then the program can be relinked against that library.

Note that this can cause problems because libtool’s compatibility requirements are actually stricter than is necessary.

Say `‘libhello’` supports interfaces 5, 16, 17, 18, and 19, and that libtool is used to link `‘test’` against `‘libhello’`.

Libtool encodes the numbers 5 and 19 in `‘test’`, and the dynamic linker will only link `‘test’` against libraries that support *every* interface between 5 and 19. So, the dynamic linker refuses to link `‘test’` against `‘libhello’`!

In order to eliminate this problem, libtool only allows libraries to declare consecutive interface numbers. So, `libhello` can declare at most that it supports interfaces 16 through 19. Then, the dynamic linker will link `test` against `libhello`.

So, libtool library versions are described by three integers:

| | |
|-----------------|---|
| <i>current</i> | The most recent interface number that this library implements. |
| <i>revision</i> | The implementation number of the <i>current</i> interface. |
| <i>age</i> | The difference between the newest and oldest interfaces that this library implements. In other words, the library implements all the interface numbers in the range from number <i>current</i> - <i>age</i> to <i>current</i> . |

If two libraries have identical *current* and *age* numbers, then the dynamic linker chooses the library with the greater *revision* number.

7.3 Updating library version information

If you want to use libtool's versioning system, then you must specify the version information to libtool using the `-version-info` flag during link mode (see [Section 4.2 \[Link mode\]](#), page 16).

This flag accepts an argument of the form `current[:revision[:age]]`. So, passing `-version-info 3:12:1` sets *current* to 3, *revision* to 12, and *age* to 1.

If either *revision* or *age* are omitted, they default to 0. Also note that *age* must be less than or equal to the *current* interface number.

Here are a set of rules to help you update your library version information:

1. Start with version information of `0:0:0` for each libtool library.
2. Update the version information only immediately before a public release of your software. More frequent updates are unnecessary, and only guarantee that the current interface number gets larger faster.
3. If the library source code has changed at all since the last update, then increment *revision* (`c:r:a` becomes `c:r+1:a`).
4. If any interfaces have been added, removed, or changed since the last update, increment *current*, and set *revision* to 0.
5. If any interfaces have been added since the last public release, then increment *age*.
6. If any interfaces have been removed since the last public release, then set *age* to 0.

Never try to set the interface numbers so that they correspond to the release number of your package. This is an abuse that only fosters misunderstanding of the purpose of library versions. Instead, use the `-release` flag (see [Section 7.4 \[Release numbers\]](#), page 38), but be warned that every release of your package will not be binary compatible with any other release.

7.4 Managing release information

Often, people want to encode the name of the package release into the shared library so that it is obvious to the user which package their programs are linked against. This convention is used especially on GNU/Linux:

```
trick$ ls /usr/lib/libbfd*
/usr/lib/libbfd.a          /usr/lib/libbfd.so.2.7.0.2
/usr/lib/libbfd.so
trick$
```

On ‘trick’, ‘/usr/lib/libbfd.so’ is a symbolic link to ‘libbfd.so.2.7.0.2’, which was distributed as a part of ‘binutils-2.7.0.2’.

Unfortunately, this convention conflicts directly with libtool’s idea of library interface versions, because the library interface rarely changes at the same time that the release number does, and the library suffix is never the same across all platforms.

So, in order to accommodate both views, you can use the ‘-release’ flag in order to set release information for libraries for which you do not want to use ‘-version-info’. For the ‘libbfd’ example, the next release that uses libtool should be built with ‘-release 2.9.0’, which will produce the following files on GNU/Linux:

```
trick$ ls /usr/lib/libbfd*
/usr/lib/libbfd-2.9.0.so  /usr/lib/libbfd.a
/usr/lib/libbfd.so
trick$
```

In this case, ‘/usr/lib/libbfd.so’ is a symbolic link to ‘libbfd-2.9.0.so’. This makes it obvious that the user is dealing with ‘binutils-2.9.0’, without compromising libtool’s idea of interface versions.

Note that this option causes a modification of the library name, so do not use it unless you want to break binary compatibility with any past library releases. In general, you should only use ‘-release’ for package-internal libraries or for ones whose interfaces change very frequently.

8 Tips for interface design

Writing a good library interface takes a lot of practice and thorough understanding of the problem that the library is intended to solve.

If you design a good interface, it won't have to change often, you won't have to keep updating documentation, and users won't have to keep relearning how to use the library.

Here is a brief list of tips for library interface design that may help you in your exploits:

Plan ahead

Try to make every interface truly minimal, so that you won't need to delete entry points very often.

Avoid interface changes

Some people love redesigning and changing entry points just for the heck of it (note: *renaming* a function is considered changing an entry point). Don't be one of those people. If you must redesign an interface, then try to leave compatibility functions behind so that users don't need to rewrite their existing code.

Use opaque data types

The fewer data type definitions a library user has access to, the better. If possible, design your functions to accept a generic pointer (that you can cast to an internal data type), and provide access functions rather than allowing the library user to directly manipulate the data. That way, you have the freedom to change the data structures without changing the interface.

This is essentially the same thing as using abstract data types and inheritance in an object-oriented system.

Use header files

If you are careful to document each of your library's global functions and variables in header files, and include them in your library source files, then the compiler will let you know if you make any interface changes by accident (see [Section 8.1 \[C header files\], page 41](#)).

Use the `static` keyword (or equivalent) whenever possible

The fewer global functions your library has, the more flexibility you'll have in changing them. Static functions and variables may change forms as often as you like. . . your users cannot access them, so they aren't interface changes.

Be careful with array dimensions

The number of elements in a global array is part of an interface, even if the header just declares `extern int foo[];`. This is because on i386 and some other SVR4/ELF systems, when an application references data in a shared library the size of that data (whatever its type) is included in the application executable. If you might want to change the size of an array or string then provide a pointer not the actual array.

8.1 Writing C header files

Writing portable C header files can be difficult, since they may be read by different types of compilers:

C++ compilers

C++ compilers require that functions be declared with full prototypes, since C++ is more strongly typed than C. C functions and variables also need to be declared with the `extern "C"` directive, so that the names aren't mangled. See [Section 6.1 \[C++ libraries\], page 35](#), for other issues relevant to using C++ with libtool.

ANSI C compilers

ANSI C compilers are not as strict as C++ compilers, but functions should be prototyped to avoid unnecessary warnings when the header file is `#included`.

non-ANSI C compilers

Non-ANSI compilers will report errors if functions are prototyped.

These complications mean that your library interface headers must use some C preprocessor magic in order to be usable by each of the above compilers.

'foo.h' in the 'tests/demo' subdirectory of the libtool distribution serves as an example for how to write a header file that can be safely installed in a system directory.

Here are the relevant portions of that file:

```
/* BEGIN_C_DECLS should be used at the beginning of your declarations,
   so that C++ compilers don't mangle their names. Use END_C_DECLS at
   the end of C declarations. */
#undef BEGIN_C_DECLS
#undef END_C_DECLS
#ifdef __cplusplus
# define BEGIN_C_DECLS extern "C" {
# define END_C_DECLS }
#else
# define BEGIN_C_DECLS /* empty */
# define END_C_DECLS /* empty */
#endif

/* PARAMS is a macro used to wrap function prototypes, so that
   compilers that don't understand ANSI C prototypes still work,
   and ANSI C compilers can issue warnings about type mismatches. */
#undef PARAMS
#ifdef __STDC__ || defined (_AIX) \
    || (defined (__mips) && defined (_SYSTYPE_SVR4)) \
    || defined(WIN32) || defined(__cplusplus)
# define PARAMS(protos) protos
#else
# define PARAMS(protos) ()
#endif
```

These macros are used in 'foo.h' as follows:

```
#ifndef FOO_H
#define FOO_H 1

/* The above macro definitions. */
#include "... "

BEGIN_C_DECLS

int foo PARAMS((void));
int hello PARAMS((void));

END_C_DECLS

#endif /* !FOO_H */
```

Note that the `#ifndef FOO_H` prevents the body of `'foo.h'` from being read more than once in a given compilation.

Also the only thing that must go outside the `BEGIN_C_DECLS/END_C_DECLS` pair are `#include` lines. Strictly speaking it is only C symbol names that need to be protected, but your header files will be more maintainable if you have a single pair of these macros around the majority of the header contents.

You should use these definitions of `PARAMS`, `BEGIN_C_DECLS`, and `END_C_DECLS` into your own headers. Then, you may use them to create header files that are valid for C++, ANSI, and non-ANSI compilers¹.

Do not be naive about writing portable code. Following the tips given above will help you miss the most obvious problems, but there are definitely other subtle portability issues. You may need to cope with some of the following issues:

- Pre-ANSI compilers do not always support the `void *` generic pointer type, and so need to use `char *` in its place.
- The `const`, `inline` and `signed` keywords are not supported by some compilers, especially pre-ANSI compilers.
- The `long double` type is not supported by many compilers.

¹ We used to recommend `__P`, `__BEGIN_DECLS` and `__END_DECLS`. This was bad advice since symbols (even preprocessor macro names) that begin with an underscore are reserved for the use of the compiler.

9 Inter-library dependencies

By definition, every shared library system provides a way for executables to depend on libraries, so that symbol resolution is deferred until runtime.

An *inter-library dependency* is one in which a library depends on other libraries. For example, if the libtool library ‘libhello’ uses the `cos` function, then it has an inter-library dependency on ‘libm’, the math library that implements `cos`.

Some shared library systems provide this feature in an internally-consistent way: these systems allow chains of dependencies of potentially infinite length.

However, most shared library systems are restricted in that they only allow a single level of dependencies. In these systems, programs may depend on shared libraries, but shared libraries may not depend on other shared libraries.

In any event, libtool provides a simple mechanism for you to declare inter-library dependencies: for every library ‘libname’ that your own library depends on, simply add a corresponding `-lname` option to the link line when you create your library. To make an example of our ‘libhello’ that depends on ‘libm’:

```
burger$ libtool --mode=link gcc -g -O -o libhello.la foo.lo hello.lo \  
             -rpath /usr/local/lib -lm
```

```
burger$
```

When you link a program against ‘libhello’, you don’t need to specify the same ‘-l’ options again: libtool will do that for you, in order to guarantee that all the required libraries are found. This restriction is only necessary to preserve compatibility with static library systems and simple dynamic library systems.

Some platforms, such as AIX, do not even allow you this flexibility. In order to build a shared library, it must be entirely self-contained (that is, have references only to symbols that are found in the ‘.lo’ files or the specified ‘-l’ libraries), and you need to specify the ‘-no-undefined’ flag. By default, libtool builds only static libraries on these kinds of platforms.

The simple-minded inter-library dependency tracking code of libtool releases prior to 1.2 was disabled because it was not clear when it was possible to link one library with another, and complex failures would occur. A more complex implementation of this concept was re-introduced before release 1.3, but it has not been ported to all platforms that libtool supports. The default, conservative behavior is to avoid linking one library with another, introducing their inter-dependencies only when a program is linked with them.

10 Dlopened modules

It can sometimes be confusing to discuss *dynamic linking*, because the term is used to refer to two different concepts:

1. Compiling and linking a program against a shared library, which is resolved automatically at run time by the dynamic linker. In this process, dynamic linking is transparent to the application.
2. The application calling functions such as `dlopen` that load arbitrary, user-specified modules at runtime. This type of dynamic linking is explicitly controlled by the application.

To mitigate confusion, this manual refers to the second type of dynamic linking as *dlopening* a module.

The main benefit to dlopening object modules is the ability to access compiled object code to extend your program, rather than using an interpreted language. In fact, `dlopen` calls are frequently used in language interpreters to provide an efficient way to extend the language.

As of version 2.2.6, `libtool` provides support for dlopened modules. However, you should indicate that your package is willing to use such support, by using the `LT_INIT` option `'dlopen'` in `'configure.ac'`. If this option is not given, `libtool` will assume no dlopening mechanism is available, and will try to simulate it.

This chapter discusses how you as a dlopen application developer might use `libtool` to generate dlopen-accessible modules.

10.1 Building modules to dlopen

On some operating systems, a program symbol must be specially declared in order to be dynamically resolved with the `dlsym` (or equivalent) function. `Libtool` provides the `'-export-dynamic'` and `'-module'` link flags (see [Section 4.2 \[Link mode\], page 16](#)), for you to make that declaration. You need to use these flags if you are linking an application program that dlopens other modules or a `libtool` library that will also be dlopened.

For example, if we wanted to build a shared library, `'hello'`, that would later be dlopened by an application, we would add `'-module'` to the other link flags:

```
burger$ libtool --mode=link gcc -module -o hello.la foo.lo \
             hello.lo -rpath /usr/local/lib -lm
burger$
```

If symbols from your *executable* are needed to satisfy unresolved references in a library you want to dlopen you will have to use the flag `'-export-dynamic'`. You should use `'-export-dynamic'` while linking the executable that calls `dlopen`:

```
burger$ libtool --mode=link gcc -export-dynamic -o helldl main.o
burger$
```

10.2 Dlpreopening

`Libtool` provides special support for dlopening `libtool` object and `libtool` library files, so that their symbols can be resolved *even on platforms without any dlopen and dlsym functions*.

Consider the following alternative ways of loading code into your program, in order of increasing “laziness”:

1. Linking against object files that become part of the program executable, whether or not they are referenced. If an object file cannot be found, then the compile time linker refuses to create the executable.
2. Declaring a static library to the linker, so that it is searched at link time in order to satisfy any undefined references in the above object files. If the static library cannot be found, then the compile time linker refuses to create the executable.
3. Declaring a shared library to the runtime linker, so that it is searched at runtime in order to satisfy any undefined references in the above files. If the shared library cannot be found, then the dynamic linker aborts the program before it runs.
4. Dlopening a module, so that the application can resolve its own, dynamically-computed references. If there is an error opening the module, or the module is not found, then the application can recover without crashing.

Libtool emulates ‘-dlopen’ on static platforms by linking objects into the program at compile time, and creating data structures that represent the program’s symbol table. In order to use this feature, you must declare the objects you want your application to dlopen by using the ‘-dlopen’ or ‘-dlpreopen’ flags when you link your program (see [Section 4.2 \[Link mode\]](#), page 16).

```
struct lt_dlsymbol { const char *name; void *address; } [Structure]
```

The *name* attribute is a null-terminated character string of the symbol name, such as “fprintf”. The *address* attribute is a generic pointer to the appropriate object, such as &fprintf.

```
struct lt_dlsymlist { const char *originator; [Structure]
                    const lt_dlsymbol symbols[]; }
```

The *originator* attribute is a null-terminated character string, naming the compilation unit that *symbols* were preloaded on behalf of. This is usually the basename of a library, ‘libltdl.la’ has a corresponding *originator* value of ‘libltdl’; if the *symbols* are for the benefit of the application proper, then *originator* is ‘@PROGRAM@’, though Libtool takes care of that detail if you use ‘LTDL_SET_PRELOADED_SYMBOLS’.

```
const lt_dlsymlist * lt_preloaded_symbols [Variable]
```

An array of *lt_symbol* structures, representing all the preloaded symbols linked into the program proper. For each module ‘-dlpreopen’ed by the Libtool linked program there is an element with the *name* of the module and a *address* of 0, followed by all symbols exported from this file. For the executable itself the special name ‘@PROGRAM@’ is used. The last element of all has a *name* and *address* of 0.

Some compilers may allow identifiers that are not valid in ANSI C, such as dollar signs. Libtool only recognizes valid ANSI C symbols (an initial ASCII letter or underscore, followed by zero or more ASCII letters, digits, and underscores), so non-ANSI symbols will not appear in *lt_preloaded_symbols*.

`int lt_dlpreload (const lt_dlsymlist *preloaded)` [Function]
 Register the list of preloaded modules *preloaded*. If *preloaded* is NULL, then all previously registered symbol lists, except the list set by `lt_dlpreload_default`, are deleted. Return 0 on success.

`int lt_dlpreload_default (const lt_dlsymlist *preloaded)` [Function]
 Set the default list of preloaded modules to *preloaded*, which won't be deleted by `lt_dlpreload`. Note that this function does *not* require `libltdl` to be initialized using `lt_dlinit` and can be used in the program to register the default preloaded modules. Instead of calling this function directly, most programs will use the macro `LTDL_SET_PRELOADED_SYMBOLS`.
 Return 0 on success.

`LTDL_SET_PRELOADED_SYMBOLS` [Macro]
 Set the default list of preloaded symbols. Should be used in your program to initialize `libltdl`'s list of preloaded modules.

```
#include <ltdl.h>

int main() {
    /* ... */
    LTDL_SET_PRELOADED_SYMBOLS();
    /* ... */
}
```

`int lt_dlpreload_callback_func (lt_dlhandle handle)` [Function Type]
 Functions of this type can be passed to `lt_dlpreload_open`, which in turn will call back into a function thus passed for each preloaded module that it opens.

`int lt_dlpreload_open (const char *originator, lt_dlpreload_callback_func *func)` [Function]
 Load all of the preloaded modules for *originator*. For every module opened in this way, call *func*.

To open all of the modules preloaded into 'libhell.1a' (presumably from within the 'libhell.a' initialisation code):

```
#define preloaded_symbols lt_libhell_LTX_preloaded_symbols

static int hell_preload_callback (lt_dlhandle handle);

int
hell_init (void)
{
    ...
    if (lt_dlpreload (&preloaded_symbols) == 0)
    {
        lt_dlpreload_open ("libhell", preload_callback);
    }
    ...
}
```

}


Note that to prevent clashes between multiple preloaded modules, the preloaded symbols are accessed via a mangled symbol name: to get the symbols preloaded into ‘libhell’, you must prefix ‘preloaded_symbols’ with ‘lt_’; the originator name, ‘libhell’ in this case; and ‘_LTX_’. That is, ‘lt_libhell_LTX_preloaded_symbols’ here.

10.3 Linking with dlopened modules

When, say, an interpreter application uses dlopened modules to extend the list of methods it provides, an obvious abstraction for the maintainers of the interpreter is to have all methods (including the built in ones supplied with the interpreter) accessed through dlopen. For one thing, the dlopening functionality will be tested even during routine invocations. For another, only one subsystem has to be written for getting methods into the interpreter.

The downside of this abstraction is, of course, that environments that provide only static linkage can’t even load the intrinsic interpreter methods. Not so! We can statically link those methods by **dlpreopening** them.

Unfortunately, since platforms such as AIX and cygwin require that all library symbols must be resolved at compile time, the interpreter maintainers will need to provide a library to both its own dlpreopened modules, and third-party modules loaded by dlopen. In itself, that is not so bad, except that the interpreter too must provide those same symbols otherwise it will be impossible to resolve all the symbols required by the modules as they are loaded. Things are even worse if the code that loads the modules for the interpreter is itself in a library – and that is usually the case for any non-trivial application. Modern platforms take care of this by automatically loading all of a module’s dependency libraries as the module is loaded (libltdl can do this even on platforms that can’t do it by themselves). In the end, this leads to problems with duplicated symbols and prevents modules from loading, and prevents the application from compiling when modules are preloaded.



Libtool has the concept of *weak library interfaces* to circumvent this problem. Recall that the code that dlopens method-provider modules for the interpreter application resides in a library: All of the modules and the dlopener library itself should be linked against the common library that resolves the module symbols at compile time. To guard against

duplicate symbol definitions, and for `dlpreopened` modules to work at all in this scenario, the `dlopener` library must declare that it provides a weak library interface to the common symbols in the library it shares with the modules. That way, when `libtool` links the **Module Loader** library with some **Dlpreopened Modules** that were in turn linked against the **Module Interface Library**, it knows that the **Module Loader** provides an already loaded **Module Interface Library** to resolve symbols for the **Dlpreopened Modules**, and doesn't ask the compiler driver to link an identical **Module Interface Library** dependency library too.

In conjunction with Automake, the 'Makefile.am' for the **Module Loader** might look like this:

```
lib_LTLIBRARIES = libinterface.la libloader.la

libinterface_la_SOURCES = interface.c interface.h
libinterface_la_LDFLAGS = -version-info 3:2:1

libloader_la_SOURCES      = loader.c
libloader_la_LDFLAGS     = -weak libinterface.la \
                          -version-info 3:2:1 \
                          -dlpreopen ../modules/intrinsics.la
libloader_la_LIBADD      = $(libinterface_la_OBJECTS)
```

And the 'Makefile.am' for the 'intrinsics.la' module in a sibling 'modules' directory might look like this:

```
AM_CPPFLAGS          = -I$(srcdir)/../libloader
AM_LDFLAGS           = -no-undefined -module -avoid-version \
                      -export-dynamic

noinst_LTLIBRARIES  = intrinsics.la

intrinsics_la_LIBADD = ../libloader/libinterface.la

../libloader/libinterface.la:
    cd ../libloader && $(MAKE) $(AM_MAKEFLAGS) libinterface.la
```

For a more complex example, see the sources of 'libltdl' in the Libtool distribution, which is built with the help of the '-weak' option.

10.4 Finding the correct name to dlopen

After a library has been linked with '-module', it can be dlopened. Unfortunately, because of the variation in library names, your package needs to determine the correct file to dlopen.

The most straightforward and flexible implementation is to determine the name at runtime, by finding the installed '.la' file, and searching it for the following lines:

```
# The name that we can dlopen.
dlname='dlname'
```

If `dlname` is empty, then the library cannot be dlopened. Otherwise, it gives the `dlname` of the library. So, if the library was installed as '/usr/local/lib/libhello.la', and the `dlname` was 'libhello.so.3', then '/usr/local/lib/libhello.so.3' should be dlopened.

If your program uses this approach, then it should search the directories listed in the `LD_LIBRARY_PATH`¹ environment variable, as well as the directory where libraries will eventually be installed. Searching this variable (or equivalent) will guarantee that your program can find its dlopened modules, even before installation, provided you have linked them using `libtool`.

10.5 Unresolved dlopen issues

The following problems are not solved by using `libtool`'s `dlopen` support:

- Dlopen functions are generally only available on shared library platforms. If you want your package to be portable to static platforms, you have to use either `libltdl` (see [Chapter 11 \[Using libltdl\], page 50](#)) or develop your own alternatives to dlopening dynamic code. Most reasonable solutions involve writing wrapper functions for the `dlopen` family, which do package-specific tricks when dlopening is unsupported or not available on a given platform.
- There are major differences in implementations of the `dlopen` family of functions. Some platforms do not even use the same function names (notably HP-UX, with its `shl_load` family).
- The application developer must write a custom search function in order to discover the correct module filename to supply to `dlopen`.

¹ `LIBPATH` on AIX, and `SHLIB_PATH` on HP-UX.

11 Using libltdl

Libtool provides a small library, called ‘libltdl’, that aims at hiding the various difficulties of dlopening libraries from programmers. It consists of a few headers and small C source files that can be distributed with applications that need dlopening functionality. On some platforms, whose dynamic linkers are too limited for a simple implementation of ‘libltdl’ services, it requires GNU DLD, or it will only emulate dynamic linking with libtool’s dlpreopening mechanism.

libltdl supports currently the following dynamic linking mechanisms:

- `dlopen` (Solaris, Linux and various BSD flavors)
- `shl_load` (HP-UX)
- `LoadLibrary` (Win16 and Win32)
- `load_add_on` (BeOS)
- `NSAddImage` or `NSLinkModule` (Darwin and Mac OS X)
- GNU DLD (emulates dynamic linking for static libraries)
- libtool’s `dlpreopen` (see see [Section 10.2 \[Dlpreopening\]](#), page 44)

libltdl is licensed under the terms of the GNU Library General Public License, with the following exception:

As a special exception to the GNU Lesser General Public License, if you distribute this file as part of a program or library that is built using GNU Libtool, you may include it under the same distribution terms that you use for the rest of that program.

11.1 How to use libltdl in your programs

The libltdl API is similar to the `dlopen` interface of Solaris and Linux, which is very simple but powerful.

To use libltdl in your program you have to include the header file ‘`ltdl.h`’:

```
#include <ltdl.h>
```

The early releases of libltdl used some symbols that violated the POSIX namespace conventions. These symbols are now deprecated, and have been replaced by those described here. If you have code that relies on the old deprecated symbol names, defining ‘`LT_NON_POSIX_NAMESPACE`’ before you include ‘`ltdl.h`’ provides conversion macros. Whichever set of symbols you use, the new API is not binary compatible with the last, so you will need to recompile your application in order to use this version of libltdl.

Note that libltdl is not well tested in a multithreaded environment, though the intention is that it should work (see [Section 11.3 \[Using libltdl in a multi threaded environment\]](#), page 57). It was reported that GNU/Linux’s glibc 2.0’s `dlopen` with ‘`RTLD_LAZY`’ (which libltdl uses by default) is not thread-safe, but this problem is supposed to be fixed in glibc 2.1. On the other hand, ‘`RTLD_NOW`’ was reported to introduce problems in multi-threaded applications on FreeBSD. Working around these problems is left as an exercise for the reader; contributions are certainly welcome.

The following macros are defined by including ‘`ltdl.h`’:

LT_PATHSEP_CHAR [Macro]
LT_PATHSEP_CHAR is the system-dependent path separator, that is, ‘;’ on Windows and ‘:’ everywhere else.

LT_DIRSEP_CHAR [Macro]
If LT_DIRSEP_CHAR is defined, it can be used as directory separator in addition to ‘/’. On Windows, this contains ‘\’.

The following types are defined in ‘ltdl.h’:

lt_dlhandle [Type]
lt_dlhandle is a module “handle”. Every lt_dlopened module has a handle associated with it.

lt_dladvise [Type]
lt_dladvise is used to control optional module loading modes. If it is not used, the default mode of the underlying system module loader is used.

lt_dlsymlist [Type]
lt_dlsymlist is a symbol list for dlpreopened modules. This structure is described in see [Section 10.2 \[Dlpreopening\]](#), page 44.

libltdl provides the following functions:

`int lt_dlinit (void)` [Function]
 Initialize libltdl. This function must be called before using libltdl and may be called several times. Return 0 on success, otherwise the number of errors.

`int lt_dlclose (void)` [Function]
 Shut down libltdl and close all modules. This function will only then shut down libltdl when it was called as many times as `lt_dlinit` has been successfully called. Return 0 on success, otherwise the number of errors.

`lt_dlhandle lt_dlopen (const char *filename)` [Function]
 Open the module with the file name *filename* and return a handle for it. `lt_dlopen` is able to open libtool dynamic modules, preloaded static modules, the program itself and native dynamic modules¹.

Unresolved symbols in the module are resolved using its dependency libraries and previously dlopened modules. If the executable using this module was linked with the `‘-export-dynamic’` flag, then the global symbols in the executable will also be used to resolve references in the module.

If *filename* is NULL and the program was linked with `‘-export-dynamic’` or `‘-dlopen self’`, `lt_dlopen` will return a handle for the program itself, which can be used to access its symbols.

If libltdl cannot find the library and the file name *filename* does not have a directory component it will additionally look in the following search paths for the module (in the following order):

1. user-defined search path: This search path can be changed by the program using the functions `lt_dlsetsearchpath`, `lt_dladdsearchdir` and `lt_dlinsertsearchdir`.
2. libltdl’s search path: This search path is the value of the environment variable `LTDL_LIBRARY_PATH`.
3. system library search path: The system dependent library search path (e.g. on Linux it is `LD_LIBRARY_PATH`).

Each search path must be a list of absolute directories separated by `LT_PATHSEP_CHAR`, for example, `"/usr/lib/mypkg:/lib/foo"`. The directory names may not contain the path separator.

If the same module is loaded several times, the same handle is returned. If `lt_dlopen` fails for any reason, it returns NULL.

`lt_dlhandle lt_dlopenext (const char *filename)` [Function]
 The same as `lt_dlopen`, except that it tries to append different file name extensions to the file name. If the file with the file name *filename* cannot be found libltdl tries to append the following extensions:

1. the libtool archive extension `‘.la’`

¹ Some platforms, notably Mac OS X, differentiate between a runtime library that cannot be opened by `lt_dlopen` and a dynamic module that can. For maximum portability you should try to ensure that you only pass `lt_dlopen` objects that have been compiled with libtool’s `‘-module’` flag.

2. the extension used for native dynamically loadable modules on the host platform, e.g., `‘.so’`, `‘.sl’`, etc.

This lookup strategy was designed to allow programs that don't have knowledge about native dynamic libraries naming conventions to be able to `dlopen` such libraries as well as libtool modules transparently.

`lt_dlhandle lt_dlopenadvise (const char *filename, [Function]
lt_dladvice advise)`

The same as `lt_dlopen`, except that it also requires an additional argument which may contain additional hints to the underlying system module loader. The `advise` parameter is opaque and can only be accessed with the functions documented below.

Note that this function does not change the content of `advise`, so unlike the other calls in this API takes a direct `lt_dladvice` type, and not a pointer to the same.

`int lt_dladvice_init (lt_dladvice *advise) [Function]`

The `advise` parameter can be used to pass hints to the module loader when using `lt_dlopenadvise` to perform the loading. The `advise` parameter needs to be initialised by this function before it can be used. Any memory used by `advise` needs to be recycled with `lt_dladvice_destroy` when it is no longer needed.

On failure, `lt_dladvice_init` returns non-zero and sets an error message that can be retrieved with `lt_dlerror`.

`int lt_dladvice_destroy (lt_dladvice *advise) [Function]`

Recycle the memory used by `advise`. For an example, see the documentation for `lt_dladvice_ext`.

On failure, `lt_dladvice_destroy` returns non-zero and sets an error message that can be retrieved with `lt_dlerror`.

`int lt_dladvice_ext (lt_dladvice *advise) [Function]`

Set the `ext` hint on `advise`. Passing an `advise` parameter to `lt_dlopenadvise` with this hint set causes it to try to append different file name extensions like `lt_dlopenext`.

The following example is equivalent to calling `lt_dlopenext (filename)`:

```
lt_dlhandle
my_dlopenext (const char *filename)
{
    lt_dlhandle handle = 0;
    lt_dladvice advise;

    if (!lt_dladvice_init (&advise) && !lt_dladvice_ext (&advise))
        handle = lt_dlopenadvise (filename, advise);

    lt_dladvice_destroy (&advise);

    return handle;
}
```

On failure, `lt_dladvise_ext` returns non-zero and sets an error message that can be retrieved with `lt_dlerror`.

`int lt_dladvise_global (lt_dladvise *advise)` [Function]

Set the `symglobal` hint on `advise`. Passing an `advise` parameter to `lt_dlopenadvise` with this hint set causes it to try to make the loaded module's symbols globally available for resolving unresolved symbols in subsequently loaded modules.

If neither the `symglobal` nor the `symlocal` hints are set, or if a module is loaded without using the `lt_dlopenadvise` call in any case, then the visibility of the module's symbols will be as per the default for the underlying module loader and OS. Even if a suitable hint is passed, not all loaders are able to act upon it in which case `lt_dlgetinfo` will reveal whether the hint was actually followed.

On failure, `lt_dladvise_global` returns non-zero and sets an error message that can be retrieved with `lt_dlerror`.

`int lt_dladvise_local (lt_dladvise *advise)` [Function]

Set the `symlocal` hint on `advise`. Passing an `advise` parameter to `lt_dlopenadvise` with this hint set causes it to try to keep the loaded module's symbols hidden so that they are not visible to subsequently loaded modules.

If neither the `symglobal` nor the `symlocal` hints are set, or if a module is loaded without using the `lt_dlopenadvise` call in any case, then the visibility of the module's symbols will be as per the default for the underlying module loader and OS. Even if a suitable hint is passed, not all loaders are able to act upon it in which case `lt_dlgetinfo` will reveal whether the hint was actually followed.

On failure, `lt_dladvise_local` returns non-zero and sets an error message that can be retrieved with `lt_dlerror`.

`int lt_dladvise_resident (lt_dladvise *advise)` [Function]

Set the `resident` hint on `advise`. Passing an `advise` parameter to `lt_dlopenadvise` with this hint set causes it to try to make the loaded module resident in memory, so that it cannot be unloaded with a later call to `lt_dlclose`.

On failure, `lt_dladvise_resident` returns non-zero and sets an error message that can be retrieved with `lt_dlerror`.

`int lt_dladvise_preload (lt_dladvise *advise)` [Function]

Set the `preload` hint on `advise`. Passing an `advise` parameter to `lt_dlopenadvise` with this hint set causes it to load only preloaded modules, so that if a suitable preloaded module is not found, `lt_dlopenadvise` will return `NULL`.

`int lt_dlclose (lt_dlhandle handle)` [Function]

Decrement the reference count on the module `handle`. If it drops to zero and no other module depends on this module, then the module is unloaded. Return 0 on success.

`void * lt_dlsym (lt_dlhandle handle, const char *name)` [Function]

Return the address in the module `handle`, where the symbol given by the null-terminated string `name` is loaded. If the symbol cannot be found, `NULL` is returned.

- const char * lt_dlerror** (*void*) [Function]
 Return a human readable string describing the most recent error that occurred from any of libltdl's functions. Return NULL if no errors have occurred since initialization or since it was last called.
- int lt_dladdsearchdir** (*const char *search_dir*) [Function]
 Append the search directory *search_dir* to the current user-defined library search path. Return 0 on success.
- int lt_dlinertsearchdir** (*const char *before*,
*const char *search_dir*) [Function]
 Insert the search directory *search_dir* into the user-defined library search path, immediately before the element starting at address *before*. If *before* is 'NULL', then *search_dir* is appending as if *lt_dladdsearchdir* had been called. Return 0 on success.
- int lt_dlsetsearchpath** (*const char *search_path*) [Function]
 Replace the current user-defined library search path with *search_path*, which must be a list of absolute directories separated by LT_PATHSEP_CHAR. Return 0 on success.
- const char *lt_dlgetsearchpath** (*void*) [Function]
 Return the current user-defined library search path.
- int lt_dlforeachfile** (*const char *search_path*,
*int (*func) (const char *filename, void * data), void * data*) [Function]
 In some applications you may not want to load individual modules with known names, but rather find all of the modules in a set of directories and load them all during initialisation. With this function you can have libltdl scan the LT_PATHSEP_CHAR-delimited directory list in *search_path* for candidates, and pass them, along with *data* to your own callback function, *func*. If *search_path* is 'NULL', then search all of the standard locations that *lt_dlopen* would examine. This function will continue to make calls to *func* for each file that it discovers in *search_path* until one of these calls returns non-zero, or until the files are exhausted. 'lt_dlforeachfile' returns the value returned by the last call made to *func*.
 For example you could define *func* to build an ordered *argv*-like vector of files using *data* to hold the address of the start of the vector.
- int lt_dlmakesresident** (*lt_dlhandle handle*) [Function]
 Mark a module so that it cannot be 'lt_dlclose'd. This can be useful if a module implements some core functionality in your project that would cause your code to crash if removed. Return 0 on success.
 If you use 'lt_dlopen (NULL)' to get a *handle* for the running binary, that handle will always be marked as resident, and consequently cannot be successfully 'lt_dlclose'd.
- int lt_dlisresident** (*lt_dlhandle handle*) [Function]
 Check whether a particular module has been marked as resident, returning 1 if it has or 0 otherwise. If there is an error while executing this function, return -1 and set an error message for retrieval with *lt_dlerror*.

11.2 Creating modules that can be dlopened

Libtool modules are created like normal libtool libraries with a few exceptions:

You have to link the module with libtool's `-module` switch, and you should link any program that is intended to dlopen the module with `-dlopen modulename.la` where possible, so that libtool can dlpreopen the module on platforms that do not support dlopening. If the module depends on any other libraries, make sure you specify them either when you link the module or when you link programs that dlopen it. If you want to disable versioning (see [Chapter 7 \[Versioning\], page 37](#)) for a specific module you should link it with the `-avoid-version` switch. Note that libtool modules don't need to have a "lib" prefix. However, Automake 1.4 or higher is required to build such modules.

Usually a set of modules provide the same interface, i.e. exports the same symbols, so that a program can dlopen them without having to know more about their internals: In order to avoid symbol conflicts all exported symbols must be prefixed with `"modulename.LTX_"` (*modulename* is the name of the module). Internal symbols must be named in such a way that they won't conflict with other modules, for example, by prefixing them with `"_modulename_"`. Although some platforms support having the same symbols defined more than once it is generally not portable and it makes it impossible to dlpreopen such modules.

libltdl will automatically cut the prefix off to get the real name of the symbol. Additionally, it supports modules that do not use a prefix so that you can also dlopen non-libtool modules.

`'foo1.c'` gives an example of a portable libtool module. Exported symbols are prefixed with `"foo1.LTX_"`, internal symbols with `"_foo1_"`. Aliases are defined at the beginning so that the code is more readable.

```
/* aliases for the exported symbols */
#define foo  foo1_LTX_foo
#define bar  foo1_LTX_bar

/* a global variable definition */
int bar = 1;

/* a private function */
int _foo1_helper() {
    return bar;
}

/* an exported function */
int foo() {
    return _foo1_helper();
}
```

The `'Makefile.am'` contains the necessary rules to build the module `'foo1.la'`:

```
...
lib_LTLIBRARIES = foo1.la

foo1_la_SOURCES = foo1.c
foo1_la_LDFLAGS = -module
```

...

11.3 Using libltdl in a multi threaded environment

Libltdl provides a wrapper around whatever dynamic run-time object loading mechanisms are provided by the host system, many of which are themselves not thread safe. Consequently libltdl cannot itself be consistently thread safe.

If you wish to use libltdl in a multithreaded environment, then you must mutex lock around libltdl calls, since they may in turn be calling non-thread-safe system calls on some target hosts.

Some old releases of libtool provided a mutex locking API that was unusable with POSIX threads, so callers were forced to lock around all libltdl API calls anyway. That mutex locking API was next to useless, and is not present in current releases.

Some future release of libtool may provide a new POSIX thread compliant mutex locking API.

11.4 Data associated with loaded modules

Some of the internal information about each loaded module that is maintained by libltdl is available to the user, in the form of this structure:

```
struct lt_dlinfo { char *filename; char *name; int ref_count; [Type]
                  int is_resident; int is_symglobal; int is_symlocal;}
```

`lt_dlinfo` is used to store information about a module. The `filename` attribute is a null-terminated character string of the real module file name. If the module is a libtool module then `name` is its module name (e.g. "libfoo" for "dir/libfoo.la"), otherwise it is set to `NULL`. The `ref_count` attribute is a reference counter that describes how often the same module is currently loaded. The remaining fields can be compared to any hints that were passed to `lt_dlopenadvise` to determine whether the underlying loader was able to follow them.

The following function will return a pointer to libltdl's internal copy of this structure for the given `handle`:

```
const lt_dlinfo * lt_dlgetinfo (lt_dlhandle handle) [Function]
```

Return a pointer to a struct that contains some information about the module `handle`. The contents of the struct must not be modified. Return `NULL` on failure.

Furthermore, in order to save you from having to keep a list of the handles of all the modules you have loaded, these functions allow you to iterate over libltdl's list of loaded modules:

```
lt_dlinterface_id [Type]
```

The opaque type used to hold the module interface details for each registered libltdl client.

```
int lt_dlhandle_interface (lt_dlhandle handle, const char *id_string) [Type]
```

Functions of this type are called to check that a handle conforms to a library's expected module interface when iterating over the global handle list. You should be

careful to write a callback function of this type that can correctly identify modules that belong to this client, both to prevent other clients from accidentally finding your loaded modules with the iterator functions below, and vice versa. The best way to do this is to check that module *handle* conforms to the interface specification of your loader using `lt_dlsym`.

The callback may be given **every** module loaded by all the libltdl module clients in the current address space, including any modules loaded by other libraries such as libltdl itself, and should return non-zero if that module does not fulfill the interface requirements of your loader.

```
int
my_interface_cb (lt_dlhandle handle, const char *id_string)
{
    char *(*module_id) (void) = NULL;

    /* A valid my_module must provide all of these symbols. */
    if (!(module_id = (char*)(*) (void)) lt_dlsym ("module_version")
        && lt_dlsym ("my_module_entrypoint"))
        return 1;

    if (strcmp (id_string, module_id()) != 0)
        return 1;

    return 0;
}
```

`lt_dlinterface_id` `lt_dlinterface_register` [Function]
 (`const char *id_string`, `lt_dlhandle_interface *iface`)

Use this function to register your interface validator with libltdl, and in return obtain a unique key to store and retrieve per-module data. You supply an *id_string* and *iface* so that the resulting `lt_dlinterface_id` can be used to filter the module handles returned by the iteration functions below. If *iface* is `NULL`, all modules will be matched.

`void` `lt_dlinterface_free` (`lt_dlinterface_id` *iface*) [Function]
 Release the data associated with *iface*.

`int` `lt_dlhandle_map` (`lt_dlinterface_id` *iface*, [Function]
`int (*func)` (`lt_dlhandle` *handle*, `void *`*data*), `void *`*data*)

For each module that matches *iface*, call the function *func*. When writing the *func* callback function, the argument *handle* is the handle of a loaded module, and *data* is the last argument passed to `lt_dlhandle_map`. As soon as *func* returns a non-zero value for one of the handles, `lt_dlhandle_map` will stop calling *func* and immediately return that non-zero value. Otherwise 0 is eventually returned when *func* has been successfully called for all matching modules.

`lt_dlhandle` `lt_dlhandle_iterate` (*lt_dlinterface_id* *iface*, [Function]
lt_dlhandle *place*)

Iterate over the module handles loaded by *iface*, returning the first matching handle in the list if *place* is NULL, and the next one on subsequent calls. If *place* is the last element in the list of eligible modules, this function returns NULL.

```
lt_dlhandle handle = 0;
lt_dlinterface_id iface = my_interface_id;

while ((handle = lt_dlhandle_iterate (iface, handle)))
{
    ...
}
```

`lt_dlhandle` `lt_dlhandle_fetch` (*lt_dlinterface_id* *iface*, [Function]
const char **module_name*)

Search through the module handles loaded by *iface* for a module named *module_name*, returning its handle if found or else NULL if no such named module has been loaded by *iface*.

However, you might still need to maintain your own list of loaded module handles (in parallel with the list maintained inside libltdl) if there were any other data that your application wanted to associate with each open module. Instead, you can use the following API calls to do that for you. You must first obtain a unique interface id from libltdl as described above, and subsequently always use it to retrieve the data you stored earlier. This allows different libraries to each store their own data against loaded modules, without interfering with one another.

`void *` `lt_dlcaller_set_data` (*lt_dlinterface_id* *key*, [Function]
lt_dlhandle *handle*, *void ** *data*)

Set *data* as the set of data uniquely associated with *key* and *handle* for later retrieval. This function returns the *data* previously associated with *key* and *handle* if any. A result of 0, may indicate that a diagnostic for the last error (if any) is available from `lt_dlerror()`.

For example, to correctly remove some associated data:

```
void *stale = lt_dlcaller_set_data (key, handle, 0);
if (stale != NULL)
{
    free (stale);
}
else
{
    char *error_msg = lt_dlerror ();

    if (error_msg != NULL)
    {
        my_error_handler (error_msg);
        return STATUS_FAILED;
    }
}
```

```
    }
}
```

```
void * lt_dlcaller_get_data (lt_dlinterface_id key, [Function]
                           lt_dlhandle handle)
```

Return the address of the data associated with *key* and *handle*, or else NULL if there is none.

Old versions of libltdl also provided a simpler, but similar, API based around `lt_dlcaller_id`. Unfortunately, it had no provision for detecting whether a module belonged to a particular interface as libltdl didn't support multiple loaders in the same address space at that time. Those APIs are no longer supported as there would be no way to stop clients of the old APIs from seeing (and accidentally altering) modules loaded by other libraries.

11.5 How to create and register new module loaders

Sometimes libltdl's many ways of gaining access to modules are not sufficient for the purposes of a project. You can write your own loader, and register it with libltdl so that `lt_dlopen` will be able to use it.

Writing a loader involves writing at least three functions that can be called by `lt_dlopen`, `lt_dlsym` and `lt_dlclose`. Optionally, you can provide a finalisation function to perform any cleanup operations when `lt_dlclose` executes, and a symbol prefix string that will be prepended to any symbols passed to `lt_dlsym`. These functions must match the function pointer types below, after which they can be allocated to an instance of `lt_user_dlloader` and registered.

Registering the loader requires that you choose a name for it, so that it can be recognised by `lt_dlloader_find` and removed with `lt_dlloader_remove`. The name you choose must be unique, and not already in use by libltdl's builtin loaders:

"dlopen" The system dynamic library loader, if one exists.

"dld" The GNU dld loader, if 'libdld' was installed when libltdl was built.

"dlpreload"
The loader for `lt_dlopening` of preloaded static modules.

The prefix "dl" is reserved for loaders supplied with future versions of libltdl, so you should not use that for your own loader names.

The following types are defined in 'ltdl.h':

```
lt_module [Type]
    lt_module is a dlloader dependent module. The dynamic module loader extensions
    communicate using these low level types.
```

```
lt_dlloader [Type]
    lt_dlloader is a handle for module loader types.
```

```
lt_user_data [Type]
    lt_user_data is used for specifying loader instance data.
```

```
struct lt_user_dlloader {const char *sym_prefix;           [Type]
    lt_module_open *module_open; lt_module_close *module_close;
    lt_find_sym *find_sym; lt_dlloader_exit *dlloader_exit; }
```

If you want to define a new way to open dynamic modules, and have the `lt_dlopen` API use it, you need to instantiate one of these structures and pass it to `lt_dlloader_add`. You can pass whatever you like in the `dlloader_data` field, and it will be passed back as the value of the first parameter to each of the functions specified in the function pointer fields.

```
lt_module lt_module_open (const char *filename)           [Type]
```

The type of the loader function for an `lt_dlloader` module loader. The value set in the `dlloader_data` field of the `struct lt_user_dlloader` structure will be passed into this function in the `loader_data` parameter. Implementation of such a function should attempt to load the named module, and return an `lt_module` suitable for passing in to the associated `lt_module_close` and `lt_sym_find` function pointers. If the function fails it should return `NULL`, and set the error message with `lt_dlseterror`.

```
int lt_module_close (lt_user_data loader_data, lt_module module) [Type]
```

The type of the unloader function for a user defined module loader. Implementation of such a function should attempt to release any resources tied up by the `module`, and then unload it from memory. If the function fails for some reason, set the error message with `lt_dlseterror` and return non-zero.

```
void * lt_find_sym (lt_module module, const char *symbol) [Type]
```

The type of the symbol lookup function for a user defined module loader. Implementation of such a function should return the address of the named `symbol` in the module `module`, or else set the error message with `lt_dlseterror` and return `NULL` if lookup fails.

```
int lt_dlloader_exit (lt_user_data loader_data)           [Type]
```

The type of the finalisation function for a user defined module loader. Implementation of such a function should free any resources associated with the loader, including any user specified data in the `dlloader_data` field of the `lt_user_dlloader`. If non-`NULL`, the function will be called by `lt_dlexit`, and `lt_dlloader_remove`.

For example:

```
int
register_myloader (void)
{
    lt_user_dlloader dlloader;

    /* User modules are responsible for their own initialisation. */
    if (myloader_init () != 0)
        return MYLOADER_INIT_ERROR;

    dlloader.sym_prefix    = NULL;
    dlloader.module_open   = myloader_open;
    dlloader.module_close  = myloader_close;
```

```
dlloader.find_sym      = myloader_find_sym;
dlloader.dlloader_exit = myloader_exit;
dlloader.dlloader_data = (lt_user_data)myloader_function;

/* Add my loader as the default module loader. */
if (lt_dlloader_add (lt_dlloader_next (NULL), &dlloader, "myloader") != 0)
    return ERROR;

return OK;
}
```

Note that if there is any initialisation required for the loader, it must be performed manually before the loader is registered – libltdl doesn't handle user loader initialisation.

Finalisation *is* handled by libltdl however, and it is important to ensure the `dlloader_exit` callback releases any resources claimed during the initialisation phase.

libltdl provides the following functions for writing your own module loaders:

```
int lt_dlloader_add (lt_dlloader *place, lt_user_dlloader *dlloader, [Function]
                    const char *loader_name)
```

Add a new module loader to the list of all loaders, either as the last loader (if *place* is NULL), else immediately before the loader passed as *place*. *loader_name* will be returned by *lt_dlloader_name* if it is subsequently passed a newly registered loader. These *loader_names* must be unique, or *lt_dlloader_remove* and *lt_dlloader_find* cannot work. Returns 0 for success.

```
/* Make myloader be the last one. */
if (lt_dlloader_add (NULL, myloader) != 0)
    perror (lt_dlerror ());
```

```
int lt_dlloader_remove (const char *loader_name) [Function]
```

Remove the loader identified by the unique name, *loader_name*. Before this can succeed, all modules opened by the named loader must have been closed. Returns 0 for success, otherwise an error message can be obtained from *lt_dlerror*.

```
/* Remove myloader. */
if (lt_dlloader_remove ("myloader") != 0)
    perror (lt_dlerror ());
```

```
lt_dlloader *lt_dlloader_next (lt_dlloader *place) [Function]
```

Iterate over the module loaders, returning the first loader if *place* is NULL, and the next one on subsequent calls. The handle is for use with *lt_dlloader_add*.

```
/* Make myloader be the first one. */
if (lt_dlloader_add (lt_dlloader_next (NULL), myloader) != 0)
    return ERROR;
```

```
lt_dlloader *lt_dlloader_find (const char *loader_name) [Function]
```

Return the first loader with a matching *loader_name* identifier, or else NULL, if the identifier is not found.

The identifiers that may be used by libltdl itself, if the host architecture supports them are *dlopen*¹, *dld* and *dlpreload*.

```
/* Add a user loader as the next module loader to be tried if
   the standard dlopen loader were to fail when lt_dlopening. */
if (lt_dlloader_add (lt_dlloader_find ("dlopen"), myloader) != 0)
    return ERROR;
```

```
const char *lt_dlloader_name (lt_dlloader *place) [Function]
```

Return the identifying name of *PLACE*, as obtained from *lt_dlloader_next* or *lt_dlloader_find*. If this function fails, it will return NULL and set an error for retrieval with *lt_dlerror*.

```
lt_user_data *lt_dlloader_data (lt_dlloader *place) [Function]
```

Return the address of the *dlloader_data* of *PLACE*, as obtained from *lt_dlloader_next* or *lt_dlloader_find*. If this function fails, it will return NULL and set an error for retrieval with *lt_dlerror*.

¹ This is used for the host dependent module loading API – *shl_load* and *LoadLibrary* for example

11.5.1 Error handling within user module loaders

`int lt_dladderror (const char *diagnostic)` [Function]

This function allows you to integrate your own error messages into `lt_dlerror`. Pass in a suitable diagnostic message for return by `lt_dlerror`, and an error identifier for use with `lt_dlseterror` is returned.

If the allocation of an identifier fails, this function returns -1.

```
int myerror = lt_dladderror ("Doh!");
if (myerror < 0)
    perror (lt_dlerror ());
```

`int lt_dlseterror (int errorcode)` [Function]

When writing your own module loaders, you should use this function to raise errors so that they are propagated through the `lt_dlerror` interface. All of the standard errors used by libltdl are declared in `'ltdl.h'`, or you can add more of your own with `lt_dladderror`. This function returns 0 on success.

```
if (lt_dlseterror (LTDL_ERROR_NO_MEMORY) != 0)
    perror (lt_dlerror ());
```

11.6 How to distribute libltdl with your package

Even though libltdl is installed together with libtool, you may wish to include libltdl in the distribution of your package, for the convenience of users of your package that don't have libtool or libltdl installed, or if you are using features of a very new version of libltdl that you don't expect your users to have yet. In such cases, you must decide which flavor of libltdl you want to use: a convenience library or an installable libtool library.

The most simplistic way to add libltdl to your package is to copy all the `'libltdl'` source files to a subdirectory within your package and to build and link them along with the rest of your sources. To help you do this, the m4 macros for Autoconf are available in `'ltdl.m4'`. You must ensure that they are available in `'aclocal.m4'` before you run Autoconf². Having made the macros available, you must add a call to the `'LTDL_INIT'` macro (after the call to `'LT_INIT'` to your package's `'configure.ac'` to perform the configure time checks required to build the library correctly. Unfortunately, this method has problems if you then try to link the package binaries with an installed libltdl, or a library that depends on libltdl, because of the duplicate symbol definitions. For example, ultimately linking against two different versions of libltdl, or against both a local convenience library and an installed libltdl is bad. Ensuring that only one copy of the libltdl sources are linked into any program is left as an exercise for the reader.

`LT_CONFIG_LTDL_DIR (DIRECTORY)` [Macro]

Declare `DIRECTORY` to be the location of the libltdl source files, for `libtoolize --ltdl` to place them. See [Section 5.5.1 \[Invoking libtoolize\], page 31](#), for more details. Provided that you add an appropriate `LT_CONFIG_LTDL_DIR` call in your `'configure.ac'` before calling `libtoolize`, the appropriate libltdl files will be installed automatically.

² We used to recommend adding the contents of `'ltdl.m4'` to `'acinclude.m4'`, but with `aclocal` from a modern Automake (1.8 or newer) and this release of libltdl that is not only unnecessary but makes it easy to forget to upgrade `'acinclude.m4'` if you move to a different release of libltdl.

LTDL_INIT (*OPTIONS*) [Macro]
 LT_WITH_LTDL [Macro]
 AC_WITH_LTDL [Macro]

AC_WITH_LTDL and LT_WITH_LTDL are deprecated names for older versions of this macro; autoupdate will update your ‘configure.ac’ file.

This macro adds the following options to the `configure` script:

‘`--with-ltdl-include INSTALLED-LTDL-HEADER-DIR`’

The `LTDL_INIT` macro will look in the standard header file locations to find the installed `libltdl` headers. If `LTDL_INIT` can’t find them by itself, the person who builds your package can use this option to tell `configure` where the installed `libltdl` headers are.

‘`--with-ltdl-lib INSTALLED-LTDL-LIBRARY-DIR`’

Similarly, the person building your package can use this option to help `configure` find the installed ‘`libltdl.la`’.

‘`--with-included-ltdl`’

If there is no installed `libltdl`, or in any case if the person building your package would rather use the `libltdl` sources shipped with the package in the subdirectory named by `LT_CONFIG_LTDL_DIR`, they should pass this option to `configure`.

If the ‘`--with-included-ltdl`’ is not passed at configure time, and an installed `libltdl` is not found³, then `configure` will exit immediately with an error that asks the user to either specify the location of an installed `libltdl` using the ‘`--with-ltdl-include`’ and ‘`--with-ltdl-lib`’ options, or to build with the `libltdl` sources shipped with the package by passing ‘`--with-included-ltdl`’.

If an installed `libltdl` is found, then `LIBLTDL` is set to the link flags needed to use it, and `LTDLINCL` to the preprocessor flags needed to find the installed headers, and `LTDLDEPS` will be empty. Note, however, that no version checking is performed. You should manually check for the `libltdl` features you need in ‘`configure.ac`’:

```
LT_INIT([dlopen])
LTDL_INIT

# The lt_dladvise_init symbol was added with libtool-2.2
if test "x$with_included_ltdl" != "xyes"; then
  save_CFLAGS="$CFLAGS"
  save_LDFLAGS="$LDFLAGS"
  CFLAGS="$CFLAGS $LTDLINCL"
  LDFLAGS="$LDFLAGS $LIBLTDL"
  AC_CHECK_LIB([ltdl], [lt_dladvise_init],
    [],
    [AC_MSG_ERROR([installed libltdl is too old])])
  LDFLAGS="$save_LDFLAGS"
  CFLAGS="$save_CFLAGS"
```

³ Even if `libltdl` is installed, ‘`LTDL_INIT`’ may fail to detect it if `libltdl` depends on symbols provided by libraries other than the C library.

fi

OPTIONS may include no more than one of the following build modes depending on how you want your project to build libltdl: ‘nonrecursive’, ‘recursive’, or ‘subproject’. In order for libtoolize to detect this option correctly, if you supply one of these arguments, they must be given literally (i.e., macros or shell variables that expand to the correct ltdl mode will not work).

‘nonrecursive’

This is how the Libtool project distribution builds the libltdl we ship and install. If you wish to use Automake to build libltdl without invoking a recursive make to descend into the libltdl subdirectory, then use this option. You will need to set your configuration up carefully to make this work properly, and you will need releases of Autoconf and Automake that support `subdir-objects` and `LIBOBJDIR` properly. In your ‘configure.ac’, add:

```
AM_INIT_AUTOMAKE([subdir-objects])
AC_CONFIG_HEADERS([config.h])
LT_CONFIG_LTDL_DIR([libltdl])
LT_INIT([dlopen])
LTDL_INIT([nonrecursive])
```

You *have to* use a config header, but it may have a name different than ‘config.h’.

Also, add the following near the top of your ‘Makefile.am’:

```
AM_CPPFLAGS =
AM_LDFLAGS =

BUILT_SOURCES =
EXTRA_DIST =
CLEANFILES =
MOSTLYCLEANFILES =

include_HEADERS =
noinst_LTLIBRARIES =
lib_LTLIBRARIES =
EXTRA_LTLIBRARIES =

include libltdl/Makefile.inc
```

Unless you build no other libraries from this ‘Makefile.am’, you will also need to change `lib_LTLIBRARIES` to assign with ‘+=’ so that the libltdl targets declared in ‘Makefile.inc’ are not overwritten.

‘recursive’

This build mode still requires that you use Automake, but (in contrast with ‘nonrecursive’) uses the more usual device of starting another `make` process in the ‘libltdl’ subdirectory. To use this mode, you should add to your ‘configure.ac’:

```

AM_INIT_AUTOMAKE
AC_CONFIG_HEADERS([config.h])
LT_CONFIG_LTDL_DIR([libltdl])
LT_INIT([dlopen])
LTDL_INIT([recursive])
AC_CONFIG_FILES([libltdl/Makefile])

```

Again, you *have to* use a config header, but it may have a name different than ‘config.h’ if you like.

Also, add this to your ‘Makefile.am’:

```
SUBDIRS = libltdl
```

‘subproject’

This mode is the default unless you explicitly add `recursive` or `nonrecursive` to your `LTDL_INIT` options; `subproject` is the only mode supported by previous releases of libltdl. Even if you do not use Autoconf in the parent project, then, in ‘subproject’ mode, still libltdl contains all the necessary files to configure and build itself – you just need to arrange for your build system to call ‘libltdl/configure’ with appropriate options, and then run `make` in the libltdl subdirectory.

If you *are* using Autoconf and Automake, then you will need to add the following to your ‘configure.ac’:

```

LT_CONFIG_LTDL_DIR([libltdl])
LTDL_INIT

```

and to ‘Makefile.am’:

```
SUBDIRS = libltdl
```

Aside from setting the libltdl build mode, there are other keywords that you can pass to `LTDL_INIT` to modify its behavior when ‘--with-included-ltdl’ has been given:

‘convenience’

This is the default unless you explicitly add `installable` to your `LTDL_INIT` options.

This keyword will cause options to be passed to the `configure` script in the subdirectory named by `LT_CONFIG_LTDL_DIR` in order to cause it to be built as a convenience library. If you’re not using automake, you will need to define `top_build_prefix`, `top_builddir`, and `top_srcdir` in your makefile so that `LIBLTDL`, `LTDLDEPS`, and `LTDLINCL` expand correctly.

One advantage of the convenience library is that it is not installed, so the fact that you use libltdl will not be apparent to the user, and it won’t overwrite a pre-installed version of libltdl the system might already have in the installation directory. On the other hand, if you want to upgrade libltdl for any reason (e.g. a bugfix) you’ll have to recompile your package instead of just replacing the shared installed version of libltdl. However, if your programs or libraries are linked with other libraries that use such a pre-installed version of libltdl, you may get linker errors or run-time crashes. Another problem is that you cannot link the convenience library into more than one libtool library, then link

a single program with those libraries, because you may get duplicate symbols. In general you can safely use the convenience library in programs that don't depend on other libraries that might use libltdl too.

`'installable'`

This keyword will pass options to the `configure` script in the subdirectory named by `LT_CONFIG_LTDL_DIR` in order to cause it to be built as an installable library. If you're not using automake, you will need to define `top_build_prefix`, `top_builddir` and `top_srcdir` in your makefile so that `LIBLTDL`, `LTDLDEPS`, and `LTDLINCL` are expanded properly.

Be aware that you could overwrite another libltdl already installed to the same directory if you use this option.

Whatever method you use, `'LTDL_INIT'` will define the shell variable `LIBLTDL` to the link flag that you should use to link with libltdl, the shell variable `LTDLDEPS` to the files that can be used as a dependency in 'Makefile' rules, and the shell variable `LTDLINCL` to the preprocessor flag that you should use to compile programs that include `'ltdl.h'`. So, when you want to link a program with libltdl, be it a convenience, installed or installable library, just use `'$(LTDLINCL)'` for preprocessing and compilation, and `'$(LIBLTDL)'` for linking.

- If your package is built using an installed version of libltdl, `LIBLTDL` will be set to the compiler flags needed to link against the installed library, `LTDLDEPS` will be empty, and `LTDLINCL` will be set to the compiler flags needed to find the libltdl header files.
- If your package is built using the convenience libltdl, `LIBLTDL` and `LTDLDEPS` will be the pathname for the convenience version of libltdl (starting with `'${top_builddir}/'` or `'${top_build_prefix}'`) and `LTDLINCL` will be `'-I'` followed by the directory that contains `'ltdl.h'` (starting with `'${top_srcdir}/'`).
- If an installable version of the included libltdl is being built, its pathname starting with `'${top_builddir}/'` or `'${top_build_prefix}'`, will be stored in `LIBLTDL` and `LTDLDEPS`, and `LTDLINCL` will be set just like in the case of convenience library.

You should probably also use the `'dlopen'` option to `LT_INIT` in your `'configure.ac'`, otherwise libtool will assume no dlopening mechanism is supported, and revert to `dlpreopening`, which is probably not what you want. Avoid using the `'-static'`, `'-static-libtool-libs'`, or `'-all-static'` switches when linking programs with libltdl. This will not work on all platforms, because the dlopening functions may not be available for static linking.

The following example shows you how to embed an installable libltdl in your package. In order to use the convenience variant, just replace the `LTDL_INIT` option `'installable'` with `'convenience'`. We assume that libltdl was embedded using `'libtoolize --ltdl'`.

`configure.ac:`

```
...
# Name the subdirectory that contains libltdl sources
LT_CONFIG_LTDL_DIR([libltdl])

# Configure libtool with dlopen support if possible
```

```
LT_INIT([dlopen])
```

```
# Enable building of the installable libltdl library
```

```
LTDL_INIT([installable])
```

```
...
```

Makefile.am:

```
...
```

```
SUBDIRS = libltdl
```

```
AM_CPPFLAGS = $(LTDLINCL)
```

```
myprog_LDFLAGS = -export-dynamic
```

```
myprog_LDADD = $(LIBLTDL) -dlopen self -dlopen foo1.la
```

```
myprog_DEPENDENCIES = $(LTDLDEPS) foo1.la
```

```
...
```

LTDL_INSTALLABLE [Macro]

AC_LIBLTDL_INSTALLABLE [Macro]

These macros are deprecated, the ‘installable’ option to LTDL_INIT should be used instead.

LTDL_CONVENIENCE [Macro]

AC_LIBLTDL_CONVENIENCE [Macro]

These macros are deprecated, the ‘convenience’ option to LTDL_INIT should be used instead.

12 Libtool's trace interface

This section describes macros whose sole purpose is to be traced using Autoconf's '`--trace`' option (see section "The Autoconf Manual" in *The Autoconf Manual*) to query the Libtool configuration of a project. These macros are called by Libtool internals and should never be called by user code; they should only be traced.

`LT_SUPPORTED_TAG` (*tag*) [Macro]

This macro is called once for each language enabled in the package. Its only argument, *tag*, is the tag-name corresponding to the language (see Section 6.2 [Tags], page 35).

You can therefore retrieve the list of all tags enabled in a project using the following command:

```
autoconf --trace 'LT_SUPPORTED_TAG:$1'
```

13 Troubleshooting

Libtool is under constant development, changing to remain up-to-date with modern operating systems. If libtool doesn't work the way you think it should on your platform, you should read this chapter to help determine what the problem is, and how to resolve it.

13.1 The libtool test suite

Libtool comes with two integrated sets of tests to check that your build is sane, that test its capabilities, and report obvious bugs in the libtool program. These tests, too, are constantly evolving, based on past problems with libtool, and known deficiencies in other operating systems.

As described in the 'README' file, you may run `make -k check` after you have built libtool (possibly before you install it) in order to make sure that it meets basic functional requirements.

13.1.1 Description of test suite

Here is a list of the current programs in the old test suite, and what they test for:

```
'cdemo-conf.test'  
'cdemo-exec.test'  
'cdemo-make.test'  
'cdemo-static.test'  
'cdemo-shared.test'  
'cdemo-undef.test'
```

These programs check to see that the 'tests/cdemo' subdirectory of the libtool distribution can be configured and built correctly.

The 'tests/cdemo' subdirectory contains a demonstration of libtool convenience libraries, a mechanism that allows build-time static libraries to be created, in a way that their components can be later linked into programs or other libraries, even shared ones.

The tests 'cdemo-make.test' and 'cdemo-exec.test' are executed three times, under three different libtool configurations: 'cdemo-conf.test' configures 'cdemo/libtool' to build both static and shared libraries (the default for platforms that support both), 'cdemo-static.test' builds only static libraries ('--disable-shared'), and 'cdemo-shared.test' builds only shared libraries ('--disable-static').

The test 'cdemo-undef.test' tests the generation of shared libraries with undefined symbols on systems that allow this.

```

'demo-conf.test'
'demo-exec.test'
'demo-inst.test'
'demo-make.test'
'demo-unst.test'
'demo-static.test'
'demo-shared.test'
'demo-nofast.test'
'demo-pic.test'
'demo-nopic.test'

```

These programs check to see that the `'tests/demo'` subdirectory of the libtool distribution can be configured, built, installed, and uninstalled correctly.

The `'tests/demo'` subdirectory contains a demonstration of a trivial package that uses libtool. The tests `'demo-make.test'`, `'demo-exec.test'`, `'demo-inst.test'` and `'demo-unst.test'` are executed four times, under four different libtool configurations: `'demo-conf.test'` configures `'demo/libtool'` to build both static and shared libraries, `'demo-static.test'` builds only static libraries (`'--disable-shared'`), and `'demo-shared.test'` builds only shared libraries (`'--disable-static'`). `'demo-nofast.test'` configures `'demo/libtool'` to disable the fast-install mode (`'--enable-fast-install=no'`). `'demo-pic.test'` configures `'demo/libtool'` to prefer building PIC code (`'--with-pic'`), `'demo-nopic.test'` to prefer non-PIC code (`'--without-pic'`).

```

'demo-deplibs.test'

```

Many systems cannot link static libraries into shared libraries. libtool uses a `deplibs_check_method` to prevent such cases. This tests checks whether libtool's `deplibs_check_method` works properly.

```

'demo-hardcode.test'

```

On all systems with shared libraries, the location of the library can be encoded in executables that are linked against it see [Section 3.3 \[Linking executables\], page 7](#). This test checks the conditions under which your system linker hard-codes the library location, and guarantees that they correspond to libtool's own notion of how your linker behaves.

```

'demo-relink.test'
'depdemo-relink.test'

```

These tests check whether variable `shlibpath_overrides_runpath` is properly set. If the test fails and `VERBOSE` is set, it will indicate what the variable should have been set to.

```

'demo-noinst-link.test'

```

Checks whether libtool will not try to link with a previously installed version of a library when it should be linking with a just-built one.

```

'depdemo-conf.test'
'depdemo-exec.test'
'depdemo-inst.test'
'depdemo-make.test'
'depdemo-unst.test'
'depdemo-static.test'
'depdemo-shared.test'
'depdemo-nofast.test'

```

These programs check to see that the `'tests/depdemo'` subdirectory of the libtool distribution can be configured, built, installed, and uninstalled correctly.

The `'tests/depdemo'` subdirectory contains a demonstration of inter-library dependencies with libtool. The test programs link some interdependent libraries.

The tests `'depdemo-make.test'`, `'depdemo-exec.test'`, `'depdemo-inst.test'` and `'depdemo-unst.test'` are executed four times, under four different libtool configurations: `'depdemo-conf.test'` configures `'depdemo/libtool'` to build both static and shared libraries, `'depdemo-static.test'` builds only static libraries (`'--disable-shared'`), and `'depdemo-shared.test'` builds only shared libraries (`'--disable-static'`). `'depdemo-nofast.test'` configures `'depdemo/libtool'` to disable the fast-install mode (`'--enable-fast-install=no'`).

```

'mdemo-conf.test'
'mdemo-exec.test'
'mdemo-inst.test'
'mdemo-make.test'
'mdemo-unst.test'
'mdemo-static.test'
'mdemo-shared.test'

```

These programs check to see that the `'tests/mdemo'` subdirectory of the libtool distribution can be configured, built, installed, and uninstalled correctly.

The `'tests/mdemo'` subdirectory contains a demonstration of a package that uses libtool and the system independent dlopen wrapper `'libltdl'` to load modules. The library `'libltdl'` provides a dlopen wrapper for various platforms (Linux, Solaris, HP/UX etc.) including support for dlpreopened modules (see [Section 10.2 \[Dlpreopening\]](#), page 44).

The tests `'mdemo-make.test'`, `'mdemo-exec.test'`, `'mdemo-inst.test'` and `'mdemo-unst.test'` are executed three times, under three different libtool configurations: `'mdemo-conf.test'` configures `'mdemo/libtool'` to build both static and shared libraries, `'mdemo-static.test'` builds only static libraries (`'--disable-shared'`), and `'mdemo-shared.test'` builds only shared libraries (`'--disable-static'`).

```

'mdemo-dryrun.test'

```

This test checks whether libtool's `'--dry-run'` mode works properly.

`'mdemo2-conf.test'`

`'mdemo2-exec.test'`

`'mdemo2-make.test'`

These programs check to see that the `'tests/mdemo2'` subdirectory of the libtool distribution can be configured, built, and executed correctly.

The `'tests/mdemo2'` directory contains a demonstration of a package that attempts to link with a library (from the `'tests/mdemo'` directory) that itself does dlopening of libtool modules.

`'link.test'`

This test guarantees that linking directly against a non-libtool static library works properly.

`'link-2.test'`

This test makes sure that files ending in `' .lo'` are never linked directly into a program file.

`'nomode.test'`

Check whether we can actually get help for libtool.

`'objectlist.test'`

Check that a nonexistent objectlist file is properly detected.

`'pdemo-conf.test'`

`'pdemo-exec.test'`

`'pdemo-inst.test'`

`'pdemo-make.test'`

These programs check to see that the `'tests/pdemo'` subdirectory of the libtool distribution can be configured, built, and executed correctly.

The `'pdemo-conf.test'` lowers the `max_cmd_len` variable in the generated libtool script to test the measures to evade command line length limitations.

`'quote.test'`

This program checks libtool's metacharacter quoting.

`'sh.test'`

Checks for some nonportable or dubious or undesired shell constructs in shell scripts.

`'suffix.test'`

When other programming languages are used with libtool (see [Chapter 6 \[Other languages\], page 35](#)), the source files may end in suffixes other than `' .c'`. This test validates that libtool can handle suffixes for all the file types that it supports, and that it fails when the suffix is invalid.

`'tagdemo-conf.test'`

`'tagdemo-exec.test'`

`'tagdemo-make.test'`

`'tagdemo-static.test'`

`'tagdemo-shared.test'`

`'tagdemo-undef.test'`

These programs check to see that the `'tests/tagdemo'` subdirectory of the libtool distribution can be configured, built, and executed correctly.

The `'tests/tagdemo'` directory contains a demonstration of a package that uses libtool's multi-language support through configuration tags. It generates a library from C++ sources, which is then linked to a C++ program.

```
'f77demo-conf.test'
'f77demo-exec.test'
'f77demo-make.test'
'f77demo-static.test'
'f77demo-shared.test'
```

These programs check to see that the `'tests/f77demo'` subdirectory of the libtool distribution can be configured, built, and executed correctly.

The `'tests/f77demo'` tests test Fortran 77 support in libtool by creating libraries from Fortran 77 sources, and mixed Fortran and C sources, and a Fortran 77 program to use the former library, and a C program to use the latter library.

```
'fcdemo-conf.test'
'fcdemo-exec.test'
'fcdemo-make.test'
'fcdemo-static.test'
'fcdemo-shared.test'
```

These programs check to see that the `'tests/fcdemo'` subdirectory of the libtool distribution can be configured, built, and executed correctly.

The `'tests/fcdemo'` is similar to the `'tests/f77demo'` directory, except that Fortran 90 is used in combination with the 'FC' interface provided by Autoconf and Automake.

13.1.2 When tests fail

Each of the tests in the old test suite are designed to produce no output when they are run via `make check`. The exit status of each program tells the 'Makefile' whether or not the test succeeded.

If a test fails, it means that there is either a programming error in libtool, or in the test program itself.

To investigate a particular test, you may run it directly, as you would a normal program. When the test is invoked in this way, it produces output that may be useful in determining what the problem is.

Another way to have the test programs produce output is to set the `VERBOSE` environment variable to 'yes' before running them. For example, `env VERBOSE=yes make check` runs all the tests, and has each of them display debugging information.

The new, Autotest-based test suite produces as output a file `'tests/testsuite.log'` which contains information about failed tests.

You can pass options to the test suite through the `make` variable `TESTSUITEFLAGS` (see section "The Autoconf Manual" in *The Autoconf Manual*).

13.2 Reporting bugs

If you think you have discovered a bug in libtool, you should think twice: the libtool maintainer is notorious for passing the buck (or maybe that should be “passing the bug”). Libtool was invented to fix known deficiencies in shared library implementations, so, in a way, most of the bugs in libtool are actually bugs in other operating systems. However, the libtool maintainer would definitely be happy to add support for somebody else’s buggy operating system. [I wish there was a good way to do winking smiley-faces in Texinfo.]

Genuine bugs in libtool include problems with shell script portability, documentation errors, and failures in the test suite (see [Section 13.1 \[Libtool test suite\]](#), page 71).

First, check the documentation and help screens to make sure that the behaviour you think is a problem is not already mentioned as a feature.

Then, you should read the Emacs guide to reporting bugs (see [section “Reporting Bugs” in *The Emacs Manual*](#)). Some of the details listed there are specific to Emacs, but the principle behind them is a general one.

Finally, send a bug report to the Libtool bug reporting address bug-libtool@gnu.org with any appropriate *facts*, such as test suite output (see [Section 13.1.2 \[When tests fail\]](#), page 75), all the details needed to reproduce the bug, and a brief description of why you think the behaviour is a bug. Be sure to include the word “libtool” in the subject line, as well as the version number you are using (which can be found by typing `libtool --version`).

14 Maintenance notes for libtool

This chapter contains information that the libtool maintainer finds important. It will be of no use to you unless you are considering porting libtool to new systems, or writing your own libtool.

14.1 Porting libtool to new systems

Before you embark on porting libtool to an unsupported system, it is worthwhile to send e-mail to the Libtool mailing list libtool@gnu.org, to make sure that you are not duplicating existing work.

If you find that any porting documentation is missing, please complain! Complaints with patches and improvements to the documentation, or to libtool itself, are more than welcome.

14.1.1 Information sources

Once it is clear that a new port is necessary, you'll generally need the following information:

canonical system name

You need the output of `config.guess` for this system, so that you can make changes to the libtool configuration process without affecting other systems.

man pages for `ld` and `cc`

These generally describe what flags are used to generate PIC, to create shared libraries, and to link against only static libraries. You may need to follow some cross references to find the information that is required.

man pages for `ld.so`, `rtld`, or equivalent

These are a valuable resource for understanding how shared libraries are loaded on the system.

man page for `ldconfig`, or equivalent

This page usually describes how to install shared libraries.

output from `ls -l /lib /usr/lib`

This shows the naming convention for shared libraries on the system, including which names should be symbolic links.

any additional documentation

Some systems have special documentation on how to build and install shared libraries.

If you know how to program the Bourne shell, then you can complete the port yourself; otherwise, you'll have to find somebody with the relevant skills who will do the work. People on the libtool mailing list are usually willing to volunteer to help you with new ports, so you can send the information to them.

To do the port yourself, you'll definitely need to modify the `libtool.m4` macros in order to make platform-specific changes to the configuration process. You should search that file for the `PORTME` keyword, which will give you some hints on what you'll need to change. In general, all that is involved is modifying the appropriate configuration variables (see [Section 14.4 \[libtool script contents\], page 84](#)).

Your best bet is to find an already-supported system that is similar to yours, and make your changes based on that. In some cases, however, your system will differ significantly from every other supported system, and it may be necessary to add new configuration variables, and modify the `ltmain.in` script accordingly. Be sure to write to the mailing list before you make changes to `ltmain.in`, since they may have advice on the most effective way of accomplishing what you want.

14.1.2 Porting inter-library dependencies support

Since version 1.2c, libtool has re-introduced the ability to do inter-library dependency on some platforms, thanks to a patch by Toshio Kuratomi badger@prtr-13.ucsc.edu. Here's a shortened version of the message that contained his patch:

The basic architecture is this: in `'libtool.m4'`, the person who writes libtool makes sure `'$deplibs'` is included in `'$archive_cmds'` somewhere and also sets the variable `'$deplibs_check_method'`, and maybe `'$file_magic_cmd'` when `'deplibs_check_method'` is `file_magic`.

`'deplibs_check_method'` can be one of five things:

`'file_magic [regex]'`

looks in the library link path for libraries that have the right libname. Then it runs `'$file_magic_cmd'` on the library and checks for a match against the extended regular expression `regex`. When `file_magic_test_file` is set by `'libtool.m4'`, it is used as an argument to `'$file_magic_cmd'` in order to verify whether the regular expression matches its output, and warn the user otherwise.

`'test_compile'`

just checks whether it is possible to link a program out of a list of libraries, and checks which of those are listed in the output of `ldd`. It is currently unused, and will probably be dropped in the future.

`'pass_all'`

will pass everything without any checking. This may work on platforms in which code is position-independent by default and inter-library dependencies are properly supported by the dynamic linker, for example, on DEC OSF/1 3 and 4.

`'none'`

It causes `deplibs` to be reassigned `'deplibs=""'`. That way `'archive_cmds'` can contain `deplibs` on all platforms, but not have `deplibs` used unless needed.

`'unknown'`

is the default for all systems unless overridden in `'libtool.m4'`. It is the same as `'none'`, but it documents that we really don't know what the correct value should be, and we welcome patches that improve it.

Then in `'ltmain.in'` we have the real workhorse: a little initialization and postprocessing (to setup/release variables for use with `eval echo libname_spec` etc.) and a case statement that decides the method that is being used. This is the real code. . . I wish I could condense it a little more, but I don't think I can without function calls. I've mostly optimized it (moved things out of loops, etc.) but there is probably some fat left. I thought I should stop while I was ahead, work on whatever bugs you discover, etc. before thinking about more than obvious optimizations.

14.2 Tested platforms

This table describes when libtool was last known to be tested on platforms where it claims to support shared libraries:

| canonical host name (tools versions) | compiler | libtool release | results |
|---|----------|-----------------|------------|
| alpha-dec-osf5.1 cc 1.3e | ok | (1.910) | |
| alpha-dec-osf4.0f | gcc | 1.3e | ok (1.910) |
| alpha-dec-osf4.0f | cc | 1.3e | ok (1.910) |
| alpha-dec-osf3.2 | gcc | 0.8 | ok |
| alpha-dec-osf3.2 | cc | 0.8 | ok |
| alpha-dec-osf2.1 | gcc | 1.2f | NS |
| alpha*-unknown-linux-gnu (egcs-1.1.2, GNU ld 2.9.1.0.23) | gcc | 1.3b | ok |
| hppa2.0w-hp-hpux11.00 | cc | 1.2f | ok |
| hppa2.0-hp-hpux10.20 | cc | 1.3.2 | ok |
| hppa1.1-hp-hpux10.20 | gcc | 1.2f | ok |
| hppa1.1-hp-hpux10.20 | cc | 1.3c | ok (1.821) |
| hppa1.1-hp-hpux10.10 | gcc | 1.2f | ok |
| hppa1.1-hp-hpux10.10 | cc | 1.2f | ok |
| hppa1.1-hp-hpux9.07 | gcc | 1.2f | ok |
| hppa1.1-hp-hpux9.07 | cc | 1.2f | ok |
| hppa1.1-hp-hpux9.05 | gcc | 1.2f | ok |
| hppa1.1-hp-hpux9.05 | cc | 1.2f | ok |
| hppa1.1-hp-hpux9.01 | gcc | 1.2f | ok |
| hppa1.1-hp-hpux9.01 | cc | 1.2f | ok |
| i*86*-beos | gcc | 1.2f | ok |
| i*86*-bsd4.0.1 (gcc-2.7.2.1) | gcc | 1.3c | ok |
| i*86*-bsd4.0 | gcc | 1.2f | ok |
| i*86*-bsd3.1 | gcc | 1.2e | NS |
| i*86*-bsd3.0 | gcc | 1.2e | NS |
| i*86*-bsd2.1 | gcc | 1.2e | NS |
| i*86-pc-cygwin (egcs-1.1 stock b20.1 compiler) | gcc | 1.3b | NS |
| i*86*-dguxR4.20MU01 | gcc | 1.2 | ok |
| i*86*-freebsd4.3 gcc 1.3e | ok | (1.912) | |
| i*86*-freebsdelf4.0 (egcs-1.1.2) | gcc | 1.3c | ok |
| i*86*-freebsdelf3.2 (gcc-2.7.2.1) | gcc | 1.3c | ok |
| i*86*-freebsdelf3.1 (gcc-2.7.2.1) | gcc | 1.3c | ok |
| i*86*-freebsdelf3.0 | gcc | 1.3c | ok |
| i*86*-freebsd3.0 | gcc | 1.2e | ok |

| | | | |
|--|-----|------|------------|
| i*86*-freebsd2.2.8 (gcc-2.7.2.1) | gcc | 1.3c | ok |
| i*86*-freebsd2.2.6 (egcs-1.1 & gcc-2.7.2.1, native ld) | gcc | 1.3b | ok |
| i*86*-freebsd2.1.5 | gcc | 0.5 | ok |
| i*86*-netbsd1.5 (egcs-1.1.2) | gcc | 1.3e | ok (1.901) |
| i*86*-netbsd1.4 (egcs-1.1.1) | gcc | 1.3c | ok |
| i*86*-netbsd1.4.3A | gcc | 1.3e | ok (1.901) |
| i*86*-netbsd1.3.3 (gcc-2.7.2.2+myc2) | gcc | 1.3c | ok |
| i*86*-netbsd1.3.2 | gcc | 1.2e | ok |
| i*86*-netbsd1.3I (egcs 1.1?) | gcc | 1.2e | ok |
| i*86*-netbsd1.2 | gcc | 0.9g | ok |
| i*86*-linux-gnu gcc 1.3e (Red Hat 7.0, gcc "2.96") | gcc | 1.3e | ok (1.901) |
| i*86*-linux-gnu gcc 1.3e (SuSE 7.0, gcc 2.95.2) | gcc | 1.3e | ok (1.911) |
| i*86*-linux-gnulibc1 | gcc | 1.2f | ok |
| i*86*-openbsd2.5 (gcc-2.8.1) | gcc | 1.3c | ok |
| i*86*-openbsd2.4 (gcc-2.8.1) | gcc | 1.3c | ok |
| i*86*-solaris2.7 (egcs-1.1.2, native ld) | gcc | 1.3b | ok |
| i*86*-solaris2.6 | gcc | 1.2f | ok |
| i*86*-solaris2.5.1 | gcc | 1.2f | ok |
| i*86-ncr-sysv4.3.03 | gcc | 1.2f | ok |
| i*86-ncr-sysv4.3.03 (cc -Hnocopyr) | cc | 1.2e | ok |
| i*86-pc-sco3.2v5.0.5 cc 1.3c | cc | 1.3c | ok |
| i*86-pc-sco3.2v5.0.5 gcc 1.3c (gcc 95q4c) | gcc | 1.3c | ok |
| i*86-pc-sco3.2v5.0.5 gcc 1.3c (egcs-1.1.2) | gcc | 1.3c | ok |
| i*86-sco-sysv5uw7.1.1 gcc 1.3e (gcc-2.95.2, SCO linker) | gcc | 1.3e | ok (1.901) |
| i*86-UnixWare7.1.0-sysv5 cc 1.3c | cc | 1.3c | ok |
| i*86-UnixWare7.1.0-sysv5 gcc 1.3c (egcs-1.1.1) | gcc | 1.3c | ok |
| m68k-next-nextstep3 | gcc | 1.2f | NS |
| m68k-sun-sunos4.1.1 (gcc-2.5.7) | gcc | 1.2f | NS |
| m88k-dg-dguxR4.12TMU01 | gcc | 1.2 | ok |
| m88k-motorola-sysv4 | gcc | 1.3 | ok |

| | | | | |
|---|-------|------------|------------|--|
| (egcs-1.1.2) | | | | |
| mips-sgi-irix6.5 | gcc | 1.2f | ok | |
| (gcc-2.8.1) | | | | |
| mips-sgi-irix6.4 | gcc | 1.2f | ok | |
| mips-sgi-irix6.3 | gcc | 1.3b | ok | |
| (egcs-1.1.2, native ld) | | | | |
| mips-sgi-irix6.3 | cc | 1.3b | ok | |
| (cc 7.0) | | | | |
| mips-sgi-irix6.2 | gcc | 1.2f | ok | |
| mips-sgi-irix6.2 | cc | 0.9 | ok | |
| mips-sgi-irix5.3 | gcc | 1.2f | ok | |
| (egcs-1.1.1) | | | | |
| mips-sgi-irix5.3 | gcc | 1.2f | NS | |
| (gcc-2.6.3) | | | | |
| mips-sgi-irix5.3 | cc | 0.8 | ok | |
| mips-sgi-irix5.2 | gcc | 1.3b | ok | |
| (egcs-1.1.2, native ld) | | | | |
| mips-sgi-irix5.2 | cc | 1.3b | ok | |
| (cc 3.18) | | | | |
| mips-sni-sysv4 cc | 1.3.5 | ok | | |
| (Siemens C-compiler) | | | | |
| mips-sni-sysv4 gcc | 1.3.5 | ok | | |
| (gcc-2.7.2.3, GNU assembler 2.8.1, native ld) | | | | |
| mipsel-unknown-openbsd2.1 | gcc | 1.0 | ok | |
| powerpc-apple-darwin6.4 | gcc | 1.5 | ok | |
| (apple dev tools released 12/2002) | | | | |
| powerpc-ibm-aix4.3.1.0 | gcc | 1.2f | ok | |
| (egcs-1.1.1) | | | | |
| powerpc-ibm-aix4.2.1.0 | gcc | 1.2f | ok | |
| (egcs-1.1.1) | | | | |
| powerpc-ibm-aix4.1.5.0 | gcc | 1.2f | ok | |
| (egcs-1.1.1) | | | | |
| powerpc-ibm-aix4.1.5.0 | gcc | 1.2f | NS | |
| (gcc-2.8.1) | | | | |
| powerpc-ibm-aix4.1.4.0 | gcc | 1.0 | ok | |
| powerpc-ibm-aix4.1.4.0 | xlc | 1.0i | ok | |
| rs6000-ibm-aix4.1.5.0 | gcc | 1.2f | ok | |
| (gcc-2.7.2) | | | | |
| rs6000-ibm-aix4.1.4.0 | gcc | 1.2f | ok | |
| (gcc-2.7.2) | | | | |
| rs6000-ibm-aix3.2.5 | gcc | 1.0i | ok | |
| rs6000-ibm-aix3.2.5 | xlc | 1.0i | ok | |
| sparc-sun-solaris2.8 gcc | 1.3e | ok (1.913) | | |
| (gcc-2.95.3 & native ld) | | | | |
| sparc-sun-solaris2.7 | gcc | 1.3e | ok (1.913) | |
| (gcc-2.95.3 & native ld) | | | | |
| sparc-sun-solaris2.6 | gcc | 1.3e | ok (1.913) | |

```

      (gcc-2.95.3 & native ld)
sparc-sun-solaris2.5.1      gcc      1.3e   ok (1.911)
sparc-sun-solaris2.5      gcc      1.3b   ok
      (egcs-1.1.2, GNU ld 2.9.1 & native ld)
sparc-sun-solaris2.5      cc       1.3b   ok
      (SC 3.0.1)
sparc-sun-solaris2.4      gcc      1.0a   ok
sparc-sun-solaris2.4      cc       1.0a   ok
sparc-sun-solaris2.3      gcc      1.2f   ok
sparc-sun-sunos4.1.4      gcc      1.2f   ok
sparc-sun-sunos4.1.4      cc       1.0f   ok
sparc-sun-sunos4.1.3_U1   gcc      1.2f   ok
sparc-sun-sunos4.1.3C     gcc      1.2f   ok
sparc-sun-sunos4.1.3      gcc      1.3b   ok
      (egcs-1.1.2, GNU ld 2.9.1 & native ld)
sparc-sun-sunos4.1.3      cc       1.3b   ok
sparc-unknown-bsdi4.0     gcc      1.2c   ok
sparc-unknown-linux-gnulibc1 gcc      1.2f   ok
sparc-unknown-linux-gnu   gcc      1.3b   ok
      (egcs-1.1.2, GNU ld 2.9.1.0.23)
sparc64-unknown-linux-gnu gcc      1.2f   ok

```

Notes:

- "ok" means "all tests passed".
- "NS" means "Not Shared", but OK for static libraries

Note: The vendor-distributed HP-UX `sed(1)` programs are horribly broken, and cannot handle libtool's requirements, so users may report unusual problems. There is no workaround except to install a working `sed` (such as GNU `sed`) on these systems.

Note: The vendor-distributed NCR MP-RAS `cc` programs emits copyright on standard error that confuse tests on size of `'confctest.err'`. The workaround is to specify `CC` when run `configure` with `CC='cc -Hnocopyr'`.

14.3 Platform quirks

This section is dedicated to the sanity of the libtool maintainers. It describes the programs that libtool uses, how they vary from system to system, and how to test for them.

Because libtool is a shell script, it can be difficult to understand just by reading it from top to bottom. This section helps show why libtool does things a certain way. Combined with the scripts themselves, you should have a better sense of how to improve libtool, or write your own.

14.3.1 References

The following is a list of valuable documentation references:

- SGI's IRIX Manual Pages can be found at <http://techpubs.sgi.com/cgi-bin/infosrch.cgi?cmd=browse&db=man>.

- Sun’s free service area (<http://www.sun.com/service/online/free.html>) and documentation server (<http://docs.sun.com/>).
- Compaq’s Tru64 UNIX online documentation is at (http://tru64unix.compaq.com/faqs/publications/pub_page/doc_list.html) with C++ documentation at (<http://tru64unix.compaq.com/cplusplus/docs/index.htm>).
- Hewlett-Packard has online documentation at (<http://docs.hp.com/index.html>).
- IBM has online documentation at (http://www.rs6000.ibm.com/resource/aix_resource/Pubs/).

14.3.2 Compilers

The only compiler characteristics that affect libtool are the flags needed (if any) to generate PIC objects. In general, if a C compiler supports certain PIC flags, then any derivative compilers support the same flags. Until there are some noteworthy exceptions to this rule, this section will document only C compilers.

The following C compilers have standard command line options, regardless of the platform:

`gcc`

This is the GNU C compiler, which is also the system compiler for many free operating systems (FreeBSD, GNU/Hurd, GNU/Linux, Lites, NetBSD, and OpenBSD, to name a few).

The ‘`-fpic`’ or ‘`-fPIC`’ flags can be used to generate position-independent code. ‘`-fPIC`’ is guaranteed to generate working code, but the code is slower on m68k, m88k, and Sparc chips. However, using ‘`-fpic`’ on those chips imposes arbitrary size limits on the shared libraries.

The rest of this subsection lists compilers by the operating system that they are bundled with:

`aix3*`

`aix4*` Most AIX compilers have no PIC flags, since AIX (with the exception of AIX for IA-64) runs on PowerPC and RS/6000 chips.¹

`hpux10*` Use ‘`+Z`’ to generate PIC.

`osf3*` Digital/UNIX 3.x does not have PIC flags, at least not on the PowerPC platform.

`solaris2*`

Use ‘`-KPIC`’ to generate PIC.

`sunos4*` Use ‘`-PIC`’ to generate PIC.

14.3.3 Reloadable objects

On all known systems, a reloadable object can be created by running `ld -r -o output.o input1.o input2.o`. This reloadable object may be treated as exactly equivalent to other objects.

¹ All code compiled for the PowerPC and RS/6000 chips (`powerpc-***`, `powerpcle-***`, and `rs6000-***`) is position-independent, regardless of the operating system or compiler suite. So, “regular objects” can be used to build shared libraries on these systems and no special PIC compiler flags are required.

14.3.4 Multiple dependencies

On most modern platforms the order in which dependent libraries are listed has no effect on object generation. In theory, there are platforms that require libraries that provide missing symbols to other libraries to be listed after those libraries whose symbols they provide.

Particularly, if a pair of static archives each resolve some of the other's symbols, it might be necessary to list one of those archives both before and after the other one. Libtool does not currently cope with this situation well, since duplicate libraries are removed from the link line by default. Libtool provides the command line option `--preserve-dup-deps` to preserve all duplicate dependencies in cases where it is necessary.

14.3.5 Archivers

On all known systems, building a static library can be accomplished by running `ar cru libname.a obj1.o obj2.o ...`, where the `.a` file is the output library, and each `.o` file is an object file.

On all known systems, if there is a program named `ranlib`, then it must be used to “bless” the created library before linking against it, with the `ranlib libname.a` command. Some systems, like Irix, use the `ar ts` command, instead.

14.4 libtool script contents

Since version 1.4, the `libtool` script is generated by `configure` (see [Section 5.4 \[Configuring\]](#), page 24). In earlier versions, `configure` achieved this by calling a helper script called `ltconfig`. From libtool version 0.7 to 1.0, this script simply set shell variables, then sourced the libtool backend, `ltmain.sh`. `ltconfig` from libtool version 1.1 through 1.3 inlined the contents of `ltmain.sh` into the generated `libtool`, which improved performance on many systems. The tests that `ltconfig` used to perform are now kept in `libtool.m4` where they can be written using Autoconf. This has the runtime performance benefits of inlined `ltmain.sh`, and improves the build time a little while considerably easing the amount of raw shell code that used to need maintaining.

The convention used for naming variables that hold shell commands for delayed evaluation, is to use the suffix `_cmd` where a single line of valid shell script is needed, and the suffix `_cmds` where multiple lines of shell script **may** be delayed for later evaluation. By convention, `_cmds` variables delimit the evaluation units with the `~` character where necessary.

Here is a listing of each of the configuration variables, and how they are used within `ltmain.sh` (see [Section 5.4 \[Configuring\]](#), page 24):

| | |
|--|------------|
| AR | [Variable] |
| The name of the system library archiver. | |
| CC | [Variable] |
| The name of the compiler used to configure libtool. This will always contain the compiler for the current language (see Section 6.2 [Tags] , page 35). | |
| ECHO | [Variable] |
| An echo program that does not interpret backslashes as an escape character. It may be given only one argument, so due quoting is necessary. | |

- LD** [Variable]
The name of the linker that libtool should use internally for reloadable linking and possibly shared libraries.
- LTCC** [Variable]
LTCFLAGS [Variable]
The name of the C compiler and C compiler flags used to configure libtool.
- NM** [Variable]
The name of a BSD- or MS-compatible program that produces listings of global symbols. For BSD `nm`, the symbols should be in one the following formats:
- ```
address C global-variable-name
address D global-variable-name
address T global-function-name
```
- For MS `dumpbin`, the symbols should be in one of the following formats:
- ```
counter size UNDEF notype External | global-var
counter address section notype External | global-var
counter address section notype ( ) External | global-func
```
- The *size* of the global variables are not zero and the *section* of the global functions are not "UNDEF". Symbols in "pick any" sections ("pick any" appears in the section header) are not global either.
- RANLIB** [Variable]
Set to the name of the `ranlib` program, if any.
- allow_undefined_flag** [Variable]
The flag that is used by ‘`archive_cmds`’ in order to declare that there will be unresolved symbols in the resulting shared library. Empty, if no such flag is required. Set to ‘`unsupported`’ if there is no way to generate a shared library with references to symbols that aren’t defined in that library.
- always_export_symbols** [Variable]
Whether libtool should automatically generate a list of exported symbols using `export_symbols_cmds` before linking an archive. Set to ‘`yes`’ or ‘`no`’. Default is ‘`no`’.
- archive_cmds** [Variable]
archive_expsym_cmds [Variable]
old_archive_cmds [Variable]
Commands used to create shared libraries, shared libraries with ‘`-export-symbols`’ and static libraries, respectively.
- old_archive_from_new_cmds** [Variable]
If the shared library depends on a static library, ‘`old_archive_from_new_cmds`’ contains the commands used to create that static library. If this variable is not empty, ‘`old_archive_cmds`’ is not used.
- old_archive_from_expsyms_cmds** [Variable]
If a static library must be created from the export symbol list in order to correctly link with a shared library, ‘`old_archive_from_expsyms_cmds`’ contains the commands

needed to create that static library. When these commands are executed, the variable *soname* contains the name of the shared library in question, and the *\$objdir/\$newlib* contains the path of the static library these commands should build. After executing these commands, libtool will proceed to link against *\$objdir/\$newlib* instead of *soname*.

| | |
|--|------------|
| build | [Variable] |
| build_alias | [Variable] |
| build_os | [Variable] |
| Set to the specified and canonical names of the system that libtool was built on. | |
| build_libtool_libs | [Variable] |
| Whether libtool should build shared libraries on this system. Set to 'yes' or 'no'. | |
| build_old_libs | [Variable] |
| Whether libtool should build static libraries on this system. Set to 'yes' or 'no'. | |
| compiler_c_o | [Variable] |
| Whether the compiler supports the '-c' and '-o' options simultaneously. Set to 'yes' or 'no'. | |
| compiler_needs_object | [Variable] |
| Whether the compiler has to see an object listed on the command line in order to successfully invoke the linker. If 'no', then a set of convenience archives or a set of object file names can be passed via linker-specific options or linker scripts. | |
| dlopen_support | [Variable] |
| Whether dlopen is supported on the platform. Set to 'yes' or 'no'. | |
| dlopen_self | [Variable] |
| Whether it is possible to dlopen the executable itself. Set to 'yes' or 'no'. | |
| dlopen_self_static | [Variable] |
| Whether it is possible to dlopen the executable itself, when it is linked statically ('-all-static'). Set to 'yes' or 'no'. | |
| exclude_expsyms | [Variable] |
| List of symbols that should not be listed in the preloaded symbols. | |
| export_dynamic_flag_spec | [Variable] |
| Compiler link flag that allows a dlopened shared library to reference symbols that are defined in the program. | |
| export_symbols_cmds | [Variable] |
| Commands to extract exported symbols from <i>libobjs</i> to the file <i>export_symbols</i> . | |
| extract_expsyms_cmds | [Variable] |
| Commands to extract the exported symbols list from a shared library. These commands are executed if there is no file <i>\$objdir/\$soname-def</i> , and should write the names of the exported symbols to that file, for the use of 'old_archive_from_expsyms_cmds'. | |

fast_install [Variable]

Determines whether libtool will privilege the installer or the developer. The assumption is that installers will seldom run programs in the build tree, and the developer will seldom install. This is only meaningful on platforms where *shlib-path-overrides-runpath* is not 'yes', so *fast_install* will be set to 'needless' in this case. If *fast_install* set to 'yes', libtool will create programs that search for installed libraries, and, if a program is run in the build tree, a new copy will be linked on-demand to use the yet-to-be-installed libraries. If set to 'no', libtool will create programs that use the yet-to-be-installed libraries, and will link a new copy of the program at install time. The default value is 'yes' or 'needless', depending on platform and configuration flags, and it can be turned from 'yes' to 'no' with the configure flag '--disable-fast-install'.

On some systems, the linker always hardcodes paths to dependent libraries into the output. In this case, *fast_install* is never set to 'yes', and relinking at install time is triggered. This also means that *DESTDIR* installation does not work as expected.

finish_cmds [Variable]

Commands to tell the dynamic linker how to find shared libraries in a specific directory.

finish_eval [Variable]

Same as *finish_cmds*, except the commands are not displayed.

fix_srcfile_path [Variable]

Expression to fix the shell variable '\$srcfile' for the compiler.

global_symbol_pipe [Variable]

A pipeline that takes the output of *NM*, and produces a listing of raw symbols followed by their C names. For example:

```
$ eval "$NM progname | $global_symbol_pipe"
D symbol1 C-symbol1
T symbol2 C-symbol2
C symbol3 C-symbol3
...
$
```

The first column contains the symbol type (used to tell data from code) but its meaning is system dependent.

global_symbol_to_cdecl [Variable]

A pipeline that translates the output of *global_symbol_pipe* into proper C declarations. Since some platforms, such as HP/UX, have linkers that differentiate code from data, data symbols are declared as data, and code symbols are declared as functions.

hardcode_action [Variable]

Either 'immediate' or 'relink', depending on whether shared library paths can be hardcoded into executables before they are installed, or if they need to be relinked.

- hardcode_direct** [Variable]
Set to 'yes' or 'no', depending on whether the linker hardcodes directories if a library is directly specified on the command line (such as '*dir/libname.a*') when *hardcode_libdir_flag_spec* is specified.
- hardcode_direct_absolute** [Variable]
Some architectures hardcode "absolute" library directories that can not be overridden by *shlibpath_var* when *hardcode_direct* is 'yes'. In that case set *hardcode_direct_absolute* to 'yes', or otherwise 'no'.
- hardcode_into_libs** [Variable]
Whether the platform supports hardcoding of run-paths into libraries. If enabled, linking of programs will be much simpler but libraries will need to be relinked during installation. Set to 'yes' or 'no'.
- hardcode_libdir_flag_spec** [Variable]
Flag to hardcode a *libdir* variable into a binary, so that the dynamic linker searches *libdir* for shared libraries at runtime. If it is empty, libtool will try to use some other hardcoding mechanism.
- hardcode_libdir_separator** [Variable]
If the compiler only accepts a single *hardcode_libdir_flag*, then this variable contains the string that should separate multiple arguments to that flag.
- hardcode_minus_L** [Variable]
Set to 'yes' or 'no', depending on whether the linker hardcodes directories specified by '-L' flags into the resulting executable when *hardcode_libdir_flag_spec* is specified.
- hardcode_shlibpath_var** [Variable]
Set to 'yes' or 'no', depending on whether the linker hardcodes directories by writing the contents of '\$*shlibpath_var*' into the resulting executable when *hardcode_libdir_flag_spec* is specified. Set to 'unsupported' if directories specified by '\$*shlibpath_var*' are searched at run time, but not at link time.
- host** [Variable]
host_alias [Variable]
host_os [Variable]
Set to the specified and canonical names of the system that libtool was configured for.
- include_expsyms** [Variable]
List of symbols that must always be exported when using *export_symbols*.
- inherit_rpath** [Variable]
Whether the linker adds runtime paths of dependency libraries to the runtime path list, requiring libtool to relink the output when installing. Set to 'yes' or 'no'. Default is 'no'.
- libext** [Variable]
The standard old archive suffix (normally 'a').

- libname_spec** [Variable]
The format of a library name prefix. On all Unix systems, static libraries are called `'libname.a'`, but on some systems (such as OS/2 or MS-DOS), the library is just called `'name.a'`.
- library_names_spec** [Variable]
A list of shared library names. The first is the name of the file, the rest are symbolic links to the file. The name in the list is the file name that the linker finds when given `'-lname'`.
- link_all_deplibs** [Variable]
Whether libtool must link a program against all its dependency libraries. Set to `'yes'` or `'no'`. Default is `'unknown'`, which is a synonym for `'yes'`.
- link_static_flag** [Variable]
Linker flag (passed through the C compiler) used to prevent dynamic linking.
- macro_version** [Variable]
macro_revision [Variable]
The release and CVS revision from which the libtool.m4 macros were taken. This is used to ensure that macros and `ltmain.sh` correspond to the same Libtool version.
- max_cmd_len** [Variable]
The approximate longest command line that can be passed to `'$SHELL'` without being truncated, as computed by `'LT_CMD_MAX_LEN'`.
- need_lib_prefix** [Variable]
Whether we can `dlopen` modules without a `'lib'` prefix. Set to `'yes'` or `'no'`. By default, it is `'unknown'`, which means the same as `'yes'`, but documents that we are not really sure about it. `'no'` means that it is possible to `dlopen` a module without the `'lib'` prefix.
- need_version** [Variable]
Whether versioning is required for libraries, i.e. whether the dynamic linker requires a version suffix for all libraries. Set to `'yes'` or `'no'`. By default, it is `'unknown'`, which means the same as `'yes'`, but documents that we are not really sure about it.
- need_locks** [Variable]
Whether files must be locked to prevent conflicts when compiling simultaneously. Set to `'yes'` or `'no'`.
- no_built_in_flag** [Variable]
Compiler flag to disable builtin functions that conflict with declaring external global symbols as `char`.
- no_undefined_flag** [Variable]
The flag that is used by `'archive_cmds'` in order to declare that there will be no unresolved symbols in the resulting shared library. Empty, if no such flag is required.
- objdir** [Variable]
The name of the directory that contains temporary libtool files.

| | |
|--|------------|
| objext | [Variable] |
| The standard object file suffix (normally 'o'). | |
| pic_flag | [Variable] |
| Any additional compiler flags for building library object files. | |
| postinstall_cmds | [Variable] |
| old_postinstall_cmds | [Variable] |
| Commands run after installing a shared or static library, respectively. | |
| postuninstall_cmds | [Variable] |
| old_postuninstall_cmds | [Variable] |
| Commands run after uninstalling a shared or static library, respectively. | |
| reload_cmds | [Variable] |
| reload_flag | [Variable] |
| Commands to create a reloadable object. | |
| runpath_var | [Variable] |
| The environment variable that tells the linker which directories to hardcode in the resulting executable. | |
| shlibpath_overrides_runpath | [Variable] |
| Indicates whether it is possible to override the hard-coded library search path of a program with an environment variable. If this is set to no, libtool may have to create two copies of a program in the build tree, one to be installed and one to be run in the build tree only. When each of these copies is created depends on the value of fast_install . The default value is 'unknown', which is equivalent to 'no'. | |
| shlibpath_var | [Variable] |
| The environment variable that tells the dynamic linker where to find shared libraries. | |
| soname_spec | [Variable] |
| The name coded into shared libraries, if different from the real name of the file. | |
| striplib | [Variable] |
| old_striplib | [Variable] |
| Command to strip a shared (striplib) or static (old_striplib) library, respectively. If these variables are empty, the strip flag in the install mode will be ignored for libraries (see Section 4.4 [Install mode] , page 19). | |
| sys_lib_dlsearch_path_spec | [Variable] |
| Expression to get the run-time system library search path. Directories that appear in this list are never hard-coded into executables. | |
| sys_lib_search_path_spec | [Variable] |
| Expression to get the compile-time system library search path. This variable is used by libtool when it has to test whether a certain library is shared or static. The directories listed in shlibpath_var are automatically appended to this list, every time libtool runs (i.e., not at configuration time), because some linkers use this variable to extend the library search path. Linker switches such as '-L' also augment the search path. | |

| | |
|---|------------|
| <code>thread_safe_flag_spec</code> | [Variable] |
| Linker flag (passed through the C compiler) used to generate thread-safe libraries. | |
| <code>version_type</code> | [Variable] |
| The library version numbering type. One of 'libtool', 'freebsd-aout', 'freebsd-elf', 'irix', 'linux', 'osf', 'sunos', 'windows', or 'none'. | |
| <code>whole_archive_flag_spec</code> | [Variable] |
| Compiler flag to generate shared objects from convenience archives. | |
| <code>wl</code> | [Variable] |
| The C compiler flag that allows libtool to pass a flag directly to the linker. Used as: <code>`\${wl}some-flag`</code> . | |

Variables ending in `'_cmds'` or `'_eval'` contain a `'~'`-separated list of commands that are `eval`ed one after another. If any of the commands return a nonzero exit status, libtool generally exits with an error message.

Variables ending in `'_spec'` are `eval`ed before being used by libtool.

14.5 Cheap tricks

Here are a few tricks that you can use in order to make maintainership easier:

- When people report bugs, ask them to use the `'--config'`, `'--debug'`, or `'--features'` flags, if you think they will help you. These flags are there to help you get information directly, rather than having to trust second-hand observation.
- Rather than reconfiguring libtool every time I make a change to `ltmain.in`, I keep a permanent libtool script in my `PATH`, which sources `ltmain.in` directly.

The following steps describe how to create such a script, where `/home/src/libtool` is the directory containing the libtool source tree, `/home/src/libtool/libtool` is a libtool script that has been configured for your platform, and `~/bin` is a directory in your `PATH`:

```
trick$ cd ~/bin
trick$ sed 's%^\(macro_version=\).*%\1@VERSION%;
          s%^\(macro_revision=\).*%\1@package_revision%;
          /^# ltmain\.sh/q' /home/src/libtool/libtool > libtool
trick$ echo '. /home/src/libtool/ltmain.in' >> libtool
trick$ chmod +x libtool
trick$ libtool --version
ltmain.sh (GNU @PACKAGE@@TIMESTAMP@) @VERSION@
```

Copyright (C) 2008 Free Software Foundation, Inc.

This is free software; see the source for copying conditions. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.
trick\$

The output of the final `'libtool --version'` command shows that the `ltmain.in` script is being used directly. Now, modify `~/bin/libtool` or `/home/src/libtool/ltmain.in` directly in order to test new changes without having to rerun `configure`.

Appendix A GNU Free Documentation License

Version 1.2, November 2002

Copyright © 2000,2001,2002 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301, USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document *free* in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or non-commercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of “copyleft”, which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The “Document”, below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as “you”. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A “Modified Version” of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A “Secondary Section” is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document’s overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The “Invariant Sections” are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released

under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none. The “Cover Texts” are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A “Transparent” copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not “Transparent” is called “Opaque”.

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The “Title Page” means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, “Title Page” means the text near the most prominent appearance of the work’s title, preceding the beginning of the body of the text.

A section “Entitled XYZ” means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as “Acknowledgements”, “Dedications”, “Endorsements”, or “History”.) To “Preserve the Title” of such a section when you modify the Document means that it remains a section “Entitled XYZ” according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and

that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.

- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
- I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.
- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section.
- O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section Entitled “Endorsements”, provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled “History” in the various original documents, forming one section Entitled “History”; likewise combine any sections Entitled “Acknowledgements”, and any sections Entitled “Dedications”. You must delete all sections Entitled “Endorsements.”

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called

an “aggregate” if the copyright resulting from the compilation is not used to limit the legal rights of the compilation’s users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document’s Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled “Acknowledgements”, “Dedications”, or “History”, the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License “or any later version” applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

```
Copyright (C) year your name.  
Permission is granted to copy, distribute and/or modify this document  
under the terms of the GNU Free Documentation License, Version 1.2  
or any later version published by the Free Software Foundation;  
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover  
Texts. A copy of the license is included in the section entitled ‘‘GNU  
Free Documentation License’’.
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the “with...Texts.” line with this:

```
with the Invariant Sections being list their titles, with  
the Front-Cover Texts being list, and with the Back-Cover Texts  
being list.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.

Index

- (
 (const char *loader_name) 63
 (lt_dloader *place) 63
 (void) 55
-
- no-suppress, libtool compile mode option 6
 -weak option 48
- .
- ‘.la’ files 6
 ‘.libs’ subdirectory 7
 ‘.lo’ files 4
- A**
- AC_CONFIG_AUX_DIR 33
 AC_CONFIG_MACRO_DIR 33
 AC_DISABLE_FAST_INSTALL 27
 AC_DISABLE_SHARED 27
 AC_DISABLE_STATIC 28
 AC_ENABLE_SHARED 27
 AC_ENABLE_STATIC 28
 AC_LIBLTDL_CONVENIENCE 69
 AC_LIBLTDL_INSTALLABLE 69
 AC_LIBTOOL_DLOPEN 27
 AC_LIBTOOL_WIN32_DLL 27
 AC_PROG_LIBTOOL 25
 AC_WITH_LTDL 65
 aclocal 29
 allow_undefined_flag 85
 always_export_symbols 85
 AM_DISABLE_SHARED 27
 AM_DISABLE_STATIC 28
 AM_ENABLE_SHARED 27
 AM_ENABLE_STATIC 28
 AM_PROG_LIBTOOL 25
 application-level dynamic linking 44, 50
 ar 6
 AR 84
 archive_cmds 85
 archive_expsym_cmds 85
 AS 29
 autoconf traces 70
 avoiding shared libraries 34
- B**
- bug reports 76
 buggy system linkers 7
 bugs, subtle ones caused by buggy linkers 7
 build 86
- build_alias 86
 build_libtool_libs 86
 build_old_libs 86
 build_os 86
- C**
- C header files, portable 41
 C++, pitfalls 35
 C++, using 35
 C, not using 35
 CC 28, 84
 cdemo-conf.test 71
 cdemo-exec.test 71
 cdemo-make.test 71
 cdemo-shared.test 71
 cdemo-static.test 71
 cdemo-undef.test 71
 CFLAGS 28
 clean mode 21
 command options, libtool 14
 command options, libtoolize 31
 compile mode 15
 compiler_c_o 86
 compiler_needs_object 86
 compiling object files 4
 complexity of library systems 2
 config.guess 31
 config.sub 31
 configuring libtool 24
 convenience libraries 12
 CPPFLAGS 28
- D**
- debugging libraries 34
 definition of libraries 3
 demo-conf.test 72
 demo-deplibs.test 72
 demo-exec.test 72
 demo-hardcode.test 72
 demo-inst.test 72
 demo-make.test 72
 demo-nofast.test 72
 demo-noinst-link.test 72
 demo-nopic.test 72
 demo-pic.test 72
 demo-relink.test 72
 demo-shared.test 72
 demo-static.test 72
 demo-unst.test 72
 depdemo-conf.test 73
 depdemo-exec.test 73
 depdemo-inst.test 73
 depdemo-make.test 73

- depdemo-nofast.test 73
 - depdemo-relink.test 72
 - depdemo-shared.test 73
 - depdemo-static.test 73
 - depdemo-unst.test 73
 - dependencies between libraries 43
 - dependency versioning 37
 - deplibs_check_method 78
 - design issues 1
 - design of library interfaces 40
 - design philosophy 1
 - developing libraries 34
 - dlclose 44, 50
 - dlerror 50
 - DLLTOOL 29
 - dlopen 44, 50
 - dlopen_self 86
 - dlopen_self_static 86
 - dlopen_support 86
 - dlopening modules 44, 50
 - dlopening, pitfalls 49
 - dlsym 44, 50
 - double-compilation, avoiding 34
 - dynamic dependencies 37
 - dynamic linking, applications 44, 50
 - dynamic modules, names 48
- E**
- ECHO 84
 - eliding shared libraries 34
 - examples of using libtool 4
 - exclude_expsyms 86
 - execute mode 19
 - export_dynamic_flag_spec 86
 - export_symbols_cmds 86
 - extract_expsyms_cmds 86
- F**
- f77demo-conf.test 75
 - f77demo-exec.test 75
 - f77demo-make.test 75
 - f77demo-shared.test 75
 - f77demo-static.test 75
 - failed tests 75
 - fast_install 87
 - fcdemo-conf.test 75
 - fcdemo-exec.test 75
 - fcdemo-make.test 75
 - fcdemo-shared.test 75
 - fcdemo-static.test 75
 - FDL, GNU Free Documentation License 92
 - file_magic 78
 - file_magic_cmd 78
 - file_magic_test_file 78
 - finish mode 20
 - finish_cmds 87
 - finish_eval 87
 - fix_srcfile_path 87
 - formal versioning 37
- G**
- global functions 40
 - global_symbol_pipe 87
 - global_symbol_to_cdecl 87
- H**
- hardcode_action 87
 - hardcode_direct 88
 - hardcode_direct_absolute 88
 - hardcode_into_libs 88
 - hardcode_libdir_flag_spec 88
 - hardcode_libdir_separator 88
 - hardcode_minus_L 88
 - hardcode_shlibpath_var 88
 - header files 40
 - host 88
 - host_alias 88
 - host_os 88
- I**
- implementation of libtool 84
 - include files, portable 41
 - include_expsyms 88
 - inferring tags 35
 - inherit_rpath 88
 - install 11
 - install mode 19
 - install-sh 31
 - installation, finishing 11
 - int 57
 - inter-library dependencies 43
 - inter-library dependency 78
- L**
- language names 35
 - languages, non-C 35
 - LD 28, 85
 - LDFLAGS 28
 - libext 88
 - libltdl 50
 - libname_spec 89
 - libraries, definition of 3
 - libraries, finishing installation 11
 - libraries, stripping 11
 - library interfaces 37
 - library interfaces, design 40
 - library object file 4
 - library_names_spec 89
 - LIBS 28
 - libtool 14

| | | | |
|--|----|----------------------------|--------|
| libtool command options | 14 | lt_dlopenadvise | 53 |
| libtool examples | 4 | lt_dlopenext | 52 |
| libtool implementation | 84 | lt_dlpreload | 46 |
| libtool libraries | 6 | lt_dlpreload_callback_func | 46 |
| libtool library versions | 37 | lt_dlpreload_default | 46 |
| libtool specifications | 1 | lt_dlpreload_open | 46 |
| libtoolize | 31 | lt_dlseterror | 64 |
| libtoolize command options | 31 | lt_dlsetsearchpath | 55 |
| LIBTOOLIZE_OPTIONS | 33 | lt_dlsym | 54 |
| link mode | 16 | lt_dlsymbol | 45 |
| link-2.test | 74 | lt_dlsymlist | 45, 51 |
| link.test | 74 | lt_find_sym | 61 |
| link_all_deplibs | 89 | LT_FUNC_DLSYM_USCORE | 22 |
| link_static_flag | 89 | LT_INIT | 25 |
| linking against installed libraries | 7 | LT_LANG | 27 |
| linking against uninstalled libraries | 8 | LT_LIB_DLOAD | 22 |
| linking with installed libtool libraries | 8 | LT_LIB_M | 22 |
| linking, dlopen | 47 | lt_module | 60 |
| linking, dlpreopen | 47 | lt_module_close | 61 |
| linking, partial | 19 | lt_module_open | 61 |
| LN_S | 29 | LT_OUTPUT | 29 |
| LT_CMD_MAX_LEN | 22 | LT_PATH_LD | 22 |
| LT_CONFIG_LTDL_DIR | 64 | LT_PATH_NM | 22 |
| LT_DIRSEP_CHAR | 51 | LT_PATHSEP_CHAR | 51 |
| lt_dladderror | 64 | lt_preloaded_symbols | 45 |
| lt_dladdsearchdir | 55 | LT_PREREQ | 25 |
| lt_dladvice | 51 | LT_SUPPORTED_TAG | 70 |
| lt_dladvice_destroy | 53 | LT_SYS_DLOPEN_DEPLIBS | 23 |
| lt_dladvice_ext | 53 | LT_SYS_DLOPEN_SELF | 23 |
| lt_dladvice_global | 54 | LT_SYS_DLSEARCH_PATH | 23 |
| lt_dladvice_init | 53 | LT_SYS_MODULE_EXT | 23 |
| lt_dladvice_local | 54 | LT_SYS_MODULE_PATH | 23 |
| lt_dladvice_preload | 54 | LT_SYS_SYMBOL_USCORE | 23 |
| lt_dladvice_resident | 54 | lt_user_data | 60 |
| lt_dlcaller_get_data | 60 | lt_user_dloader | 61 |
| lt_dlcaller_set_data | 59 | LT_WITH_LTDL | 65 |
| lt_dlclose | 54 | LTCC | 85 |
| lt_dlerror | 55 | LTCFLAGS | 85 |
| lt_dlexit | 52 | LTDL_CONVENIENCE | 69 |
| lt_dlforeachfile | 55 | LTDL_INIT | 65 |
| lt_dlgetinfo | 57 | LTDL_INSTALLABLE | 69 |
| lt_dlhandle | 51 | LTDL_SET_PRELOADED_SYMBOLS | 46 |
| lt_dlhandle_fetch | 59 | LTDLIBOBS | 33 |
| lt_dlhandle_iterate | 59 | LTLIBRARIES | 23 |
| lt_dlhandle_map | 58 | ltmain.sh | 31 |
| lt_dlinfo | 57 | | |
| lt_dlinit | 52 | | |
| lt_dlinsertsearchdir | 55 | | |
| lt_dlinterface_free | 58 | | |
| lt_dlinterface_id | 57 | | |
| lt_dlinterface_register | 58 | | |
| lt_dlisresident | 55 | | |
| lt_dlloader | 60 | | |
| lt_dlloader_add | 63 | | |
| lt_dlloader_exit | 61 | | |
| lt_dlloader_remove | 63 | | |
| lt_dlmakeresident | 55 | | |
| lt_dlopen | 52 | | |
| | | M | |
| | | macro_revision | 89 |
| | | macro_version | 89 |
| | | Makefile | 23 |
| | | Makefile.am | 23 |
| | | Makefile.in | 23 |
| | | max_cmd_len | 89 |
| | | mdemo-conf.test | 73 |
| | | mdemo-dryrun.test | 73 |
| | | mdemo-exec.test | 73 |
| | | mdemo-inst.test | 73 |

mdemo-make.test 73
 mdemo-shared.test 73
 mdemo-static.test 73
 mdemo-unst.test 73
 mdemo2-conf.test 74
 mdemo2-exec.test 74
 mdemo2-make.test 74
 mode, clean 21
 mode, compile 15
 mode, execute 19
 mode, finish 20
 mode, install 19
 mode, link 16
 mode, uninstall 20
 modules, dynamic 44, 50
 motivation for writing libtool 1

N

names of dynamic modules 48
 need_lib_prefix 89
 need_locks 89
 need_version 89
 NM 28, 85
 no_builtin_flag 89
 no_undefined_flag 89
 nomode.test 74
 none 78

O

objdir 89
 OBJDUMP 29
 object files, compiling 4
 object files, library 4
 objectlist.test 74
 object 90
 old_archive_cmds 85
 old_archive_from_expsyms_cmds 85
 old_archive_from_new_cmds 85
 old_postinstall_cmds 90
 old_postuninstall_cmds 90
 old_striplib 90
 opaque data types 40
 options, libtool command 14
 options, libtoolize command 31
 other implementations, flaws in 2

P

partial linking 19
 pass_all 78
 pdemo-conf.test 74
 pdemo-exec.test 74
 pdemo-inst.test 74
 pdemo-make.test 74
 PIC (position-independent code) 4
 pic_flag 90

pitfalls using C++ 35
 pitfalls with dlopen 49
 portable C headers 41
 position-independent code 4
 postinstall_cmds 90
 postinstallation 11
 postuninstall_cmds 90
 problem reports 76
 problems, blaming somebody else for 71
 problems, solving 71
 program wrapper scripts 8

Q

quote.test 74

R

ranlib 6
 RANLIB 28, 85
 reload_cmds 90
 reload_flag 90
 renaming interface functions 40
 reporting bugs 76
 reusability of library systems 2
 runpath_var 90

S

saving time 34
 security problems with buggy linkers 7
 sh.test 74
 shared libraries, not using 34
 shared library versions 37
 shl_load 44, 50
 shlibpath_overrides_runpath 90
 shlibpath_var 90
 solving problems 71
 soname_spec 90
 specifications for libtool 1
 standalone binaries 13
 static linking 12
 strip 10
 striplib 90
 stripping libraries 11
 su 10
 suffix.test 74
 sys_lib_dlsearch_path_spec 90
 sys_lib_search_path_spec 90

T

tag names 35
 tagdemo-conf.test 74
 tagdemo-exec.test 74
 tagdemo-make.test 74
 tagdemo-shared.test 74
 tagdemo-static.test 74

tagdemo-undef.test 74
test suite 71
test_compile 78
tests, failed 75
thread_safe_flag_spec 91
time, saving 34
trace interface 70
tricky design issues 1
trouble with C++ 35
trouble with dlopen 49
troubleshooting 71

U

undefined symbols, allowing 16

uninstall mode 20
unknown 78
unresolved symbols, allowing 16
using shared libraries, not 34

V

version_type 91
versioning, formal 37

W

whole_archive_flag_spec 91
wl 91
wrapper scripts for programs 8

Table of Contents

| | | |
|----------|--|-----------|
| 1 | Introduction | 1 |
| 1.1 | Motivation for writing libtool | 1 |
| 1.2 | Implementation issues | 1 |
| 1.3 | Other implementations | 2 |
| 1.4 | A postmortem analysis of other implementations | 2 |
| 2 | The libtool paradigm | 3 |
| 3 | Using libtool | 4 |
| 3.1 | Creating object files | 4 |
| 3.2 | Linking libraries | 6 |
| 3.3 | Linking executables | 7 |
| 3.4 | Debugging executables | 9 |
| 3.5 | Installing libraries | 10 |
| 3.6 | Installing executables | 12 |
| 3.7 | Linking static libraries | 12 |
| 4 | Invoking libtool | 14 |
| 4.1 | Compile mode | 15 |
| 4.2 | Link mode | 16 |
| 4.3 | Execute mode | 19 |
| 4.4 | Install mode | 19 |
| 4.5 | Finish mode | 20 |
| 4.6 | Uninstall mode | 20 |
| 4.7 | Clean mode | 21 |
| 5 | Integrating libtool with your package | 22 |
| 5.1 | Autoconf macros exported by libtool | 22 |
| 5.2 | Writing ‘Makefile’ rules for libtool | 23 |
| 5.3 | Using Automake with libtool | 23 |
| 5.4 | Configuring libtool | 24 |
| 5.4.1 | The LT_INIT macro | 25 |
| 5.4.2 | Platform-specific configuration notes | 30 |
| 5.5 | Including libtool in your package | 31 |
| 5.5.1 | Invoking libtoolize | 31 |
| 5.5.2 | Autoconf and LTLIBOBJS | 33 |
| 5.6 | Static-only libraries | 34 |
| 6 | Using libtool with other languages | 35 |
| 6.1 | Writing libraries for C++ | 35 |
| 6.2 | Tags | 35 |

| | | |
|-----------|---|-----------|
| 7 | Library interface versions | 37 |
| 7.1 | What are library interfaces? | 37 |
| 7.2 | Libtool's versioning system | 37 |
| 7.3 | Updating library version information | 38 |
| 7.4 | Managing release information | 38 |
| 8 | Tips for interface design | 40 |
| 8.1 | Writing C header files | 41 |
| 9 | Inter-library dependencies | 43 |
| 10 | Dlopened modules | 44 |
| 10.1 | Building modules to dlopen | 44 |
| 10.2 | Dlpreopening | 44 |
| 10.3 | Linking with dlopened modules | 47 |
| 10.4 | Finding the correct name to dlopen | 48 |
| 10.5 | Unresolved dlopen issues | 49 |
| 11 | Using libltdl | 50 |
| 11.1 | How to use libltdl in your programs | 50 |
| 11.2 | Creating modules that can be dlopened | 56 |
| 11.3 | Using libltdl in a multi threaded environment | 57 |
| 11.4 | Data associated with loaded modules | 57 |
| 11.5 | How to create and register new module loaders | 60 |
| 11.5.1 | Error handling within user module loaders | 64 |
| 11.6 | How to distribute libltdl with your package | 64 |
| 12 | Libtool's trace interface | 70 |
| 13 | Troubleshooting | 71 |
| 13.1 | The libtool test suite | 71 |
| 13.1.1 | Description of test suite | 71 |
| 13.1.2 | When tests fail | 75 |
| 13.2 | Reporting bugs | 75 |

| | | |
|--|--|-----------|
| 14 | Maintenance notes for libtool..... | 77 |
| 14.1 | Porting libtool to new systems | 77 |
| 14.1.1 | Information sources | 77 |
| 14.1.2 | Porting inter-library dependencies support | 78 |
| 14.2 | Tested platforms | 79 |
| 14.3 | Platform quirks | 82 |
| 14.3.1 | References | 82 |
| 14.3.2 | Compilers | 83 |
| 14.3.3 | Reloadable objects | 83 |
| 14.3.4 | Multiple dependencies | 84 |
| 14.3.5 | Archivers | 84 |
| 14.4 | libtool script contents | 84 |
| 14.5 | Cheap tricks | 91 |
| Appendix A GNU Free Documentation License | | |
| | | 92 |
| | | |
| Index | | 99 |